



Dry Fix™

Damp Proof Course



Dry Fix™ is a thick embossed polyethylene film and approved for use for separating timber, wood-based products and metal from concrete, masonry or brick; and, as a moisture barrier and flashing in masonry veneer constructed in accordance with NZBC Acceptable Solution E2/AS2 and NZS 4229.

Dry Fix™ - Advantages

- Instant shape forming
- An alternative for Bituminous DPC
- Does not react with solvent treated timber
- Inert to most solvents
- Permanent life span non-degradable
- Easy to use
- Cost effective

Technical Details

- Embossed both sides to a minimum thickness of 750 um
- CodeMark Certified
- Manufactured to AS/NZS2904 - 1995
- Impact resistant
- Low Slip with a kinetic coefficient of friction
- Non-Slip as product is double embossed
- Roll core made from recycled cardboard
- Complies to the NZBC



Description	Roll Length	Bunnings Code
Dry Fix 50mm	30m	00279105
Dry Fix 75mm	30m	00279108
Dry Fix 90mm	30m	00258016
Dry Fix 100mm	30m	00279114
Dry Fix 150mm	30m	00258017
Dry Fix 200mm	30m	00279120
Dry Fix 250mm	30m	00279127
Dry Fix 300mm	30m	00279144

