



SAFEGUARD 180° PEEL & SEAL TAPE

MULTIPURPOSE WATERPROOFING TAPE FOR INTERNAL AND EXTERNAL APPLICATIONS.

5m x 80mm

APPLICATION:

Unroll the Cemix® Safeguard 180 Peel and Seal Tape and measure the required length. Cut the tape using scissors or a sharp cutter knife. Place roll over the area to be sealed and while slowly unwinding, remove release paper and position the tacky side directly over the area to be sealed. For best results, remove release paper as the tape is being unrolled and adhered into position. It is not recommended to remove total length of release paper before adhering into position. Press tape into position with a spatula, roller, or cloth, ensuring air pockets and creases are pushed out and removed. Finishes can be applied immediately after the tape is in place. It is recommended to apply one of the Cemix® waterproofing membranes Cemix® Safeguard 180 Peel and Seal Tape directly over the tape surface.

APPEARANCE:

Butyl self adhesive tape.

APPLICATION TEMP:

5 - 30°C

PACKAGING:

5m x 80mm rolls.

STORAGE & SHELF LIFE:

Cemix® Safeguard 180 Peel and Seal Tape needs to be stored in a cool dry place.

CLEANING:

Clean all tools with water & brush immediately after use.

DESCRIPTION:

Cemix® Safeguard 180 Peel and Seal Tape is a multi-purpose self adhesive tape designed for flashing and sealing a variety of surfaces. The outstanding adhesion and waterproof properties enables high quality sealing over a range of non-porous surfaces. Suitable for use over internal and external surfaces, Cemix® Safeguard 180 Peel and Seal Tape displays a high degree of tear and rupture resistance, withstanding flexing and vibration on many building substrates. Cemix® Safeguard 180 Peel and Seal Tape provides an instant seal to the surface it is applied to, avoiding down time for drying or curing. Ideally suited for roofing, flashing and repair applications, Cemix® Safeguard 180 Peel and Seal Tape is versatile for numerous applications. Designed to be finished over with Cemix® membranes, adhesives, membranes, coatings, mortars and renders.

TYPICAL APPLICATION/USES:

- Sealing roof sheet joints.
- Sealing joints between structural floor sheeting on decks and balconies.
- Flashing metal surfaces.
- Patching pin holes on roofing and gutter surfaces.
- Sealing and detailing over plumbing pipes, PVC penetrations etc.
- Waterproofing junctions before tiling.
- Sealing and detailing external lightweight sheeting abutments before rendering & texturing.
- Crack repairs on floors before tiling, screeds and toppings.

ADVANTAGES:

- Ease of application.
- No primer required (see substrate preparation).
- Excellent adhesive properties over metals, plastics, glazed surfaces and dense surfaces.
- Outstanding adhesion retention at low temperatures.
- Instant sealing properties, no drying required.
- Rupture and tear resistant.
- Solvent free and non-toxic.
- Ability to cover over Cemix® membranes and adhesives.
- Compatible with cement based finishes. E.g. tile adhesives, renders and textures.

SUBSTRATE PREPARATION:

Ensure the surface is clean, free of dust, loose foreign matter and debris. Surfaces must be free of oil, wax or grease residues. Wiping over with alcohol based cleaner is recommended so optimum adhesion can be achieved. If applying over dusty concrete, masonry surfaces, prime first with Cemix® primer to stabilise surface. After priming, apply a neutral cure non-paintable sealant to all wall and floor junctions and sheet joints.

MATERIALS:

Cemix® Safeguard 180 Peel and Seal Tape is a Butyl Self Adhesive Tape.

LIMITATIONS:

- Surfaces must be dry, do not apply on damp surfaces.
- Not to be used as an exposed flashing, must be finished over with a surface coating.
- Not to be used as a trafficable surface.
- Not to be used over expansion joints.
- Concrete with residual moisture must be sealed with Cemix® primer before applying tape.

CEMIX LTD
19 ALFRED STREET
ONEHUNGA 1061
AUCKLAND
NEW ZEALAND
0800 ASK CEMIX
WWW.CEMIX.CO.NZ



- When applying over metals, ensure surface is rust free and if required treat rust before applying tape.
- Do not apply solvent-based surface finishes or adhesives directly over the tape surface.

PRECAUTION:

- Can be painted however paints that cover must be compatible and able to flex with the tape or cracking will occur.

SAFETY

Avoid contact with eyes & skin. Wear suitable protective clothing, gloves, eye protection & barrier cream. Wash thoroughly after handling & store any leftover material properly.

FIRST AID

Irrigate eyes & skin with plenty of water & seek medical advice immediately.

SPILLS AND LEAKS:

Keep out of sewers & storm water drains & dispose of any leftover material as trade waste in accordance with local authority guidelines.

DISCLAIMER:

Recommendations & advice regarding the use of this product are to be taken as a guide only. Other than as appears on this products packaging, CEMIX® LTD does not give any warranty express or implied as to the suitability of this product for your particular use, because the usage of this product is beyond the control of CEMIX® LTD. If you need advice concerning the use of suitability of this product for your particular application, please contact CEMIX® LTD first.

CEMIX LTD
19 ALFRED STREET
ONEHUNGA 1061
AUCKLAND
NEW ZEALAND
0800 ASK CEMIX
WWW.CEMIX.CO.NZ

