

August 2022 | Page Number 1



MORTARFLEX PLUS

CONCENTRATED POWDERED PLASTICISER FOR EXTERIOR USE PLASTER & MORTAR

AVAILABLE SIZES: 200G | 600G | 1.5KG



NOTE: Due to updates in progress, packaging may vary.

DESCRIPTION:

CEMIX® MORTARFLEX PLUS is a highly concentrated, powdered plasticiser, designed to improve the workability and adhesion of exterior use plaster and mortar.

TYPICAL USES:

CEMIX® MORTARFLEX PLUS can be used as an air entraining additive for exterior use plaster and mortar, removing the need for adding lime to the mix.

ADVANTAGES:

- · Improves workability and bond strength
- Allows for quicker application
- · Reduced cracking from shrinkage
- Minimises water absorption
- · Minimises efflorescence
- Freeze resistant

DOSAGE:

5g per kg of cement

PREPARATION:

Refer to the manufacturer's recommendations for the exterior use plaster or mortar being used.

MIXING:

1. Add the product directly to the mix during mixing. Use 5g of product per kg of cement.

Note: Do not aerate the mixture by stirring over vigorously or for too long. In general, a maximum of 3 minutes is recommended. Accurate measuring is essential as too much product can weaken the mix - use less product rather than more.

APPLICATION:

Refer to the manufacturer's recommendations for the exterior use plaster or mortar being used.

CLEANING:

Clean tools with water immediately after use.

STORAGE & SHELF LIFE:

Up to 12 months when stored in the original, unopened packaging, in a dry place at 23°C and 50% relative humidity.

LIMITATIONS:

Accurate measuring is essential as too much product can weaken the mix - use less product rather than more.

If lime is required in the mix, use CEMIX® CEMPLUS.

If your project requires Building Consent, please email info@ cemix.co.nz about the suitability of this product before use.

Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at

DANGER

HAZARD STATEMENTS:


Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction.

SAFETY INSTRUCTIONS:

Wear protective gloves/protective clothing/eye protection/ face protection. Avoid breathing dust/fumes. Contaminated work clothing should not be allowed out of the workplace.







August 2022 | Page Number 2

MORTARFLEX PLUS

INGREDIENTS:

Limestone, CAS: 1317-65-3, 40-45%; Modified cellulose, proprietary, CAS: NA, 20-25%, Portland Cement, CAS: 65997-15-1, 4-5%; Ingredients determined not to be hazardous, CAS: NA, <25%

DISCLAIMER:

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX® PRODUCTS LTD does not give any warranty expressed or implied as to suitability for any particular use. For all advice concerning the use or suitability of this product for a particular application, please contact CEMIX® PRODUCTS LTD. If this product is defective. please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD, who will refund or replace it at no cost, in accordance with the requirements of the Consumer Guarantees Act.

SCAN QR CODE FOR MORE PRODUCT INFORMATION



CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061 AUCKLAND NEW ZEALAND 0800 ASK CEMIX | +64 09 636 1000 WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pintrest/CemixNZ



YouTube/CemixVideos

