



Reinforcing Fabric with Bond Breaker

Self-adhesive, non-woven, polyester fabric for strengthening membranes.

DESCRIPTION

Crommelin[®] Reinforcing Fabric with Bond Breaker is a 100mm wide self-adhesive non-woven polyester fabric. It incorporates a self-adhesive portion (central 1/3 of tape) that acts as a bond-breaker over joints, cracks or other areas of movement.

When used in conjunction with approved liquid applied waterproofing membranes the combined system will meet the requirements of AS 3740 "Waterproofing of Wet Areas Within Residential Buildings".

FEATURES AND BENEFITS

- Breaks bond of membrane system to allow movement at joints.
- Does not crease during installation.
- Bridges gaps.
- Strengthens membranes by increasing tensile strength and puncture resistance.
- Flexible.
- Easy to wet out.
- Outstanding conformability.
- High grab tensile strength.
- UV stable.
- Rot proof when buried.

AREAS OF USE

Reinforcing Fabric with Bond Breaker is suitable for use in the following areas:

- Around Pipes & Penetrations.
- Internal Corners.
- Over Cracks & Construction Joints



SUITABLE SUBSTRATES

Reinforcing Fabric with Bond Breaker is suitable for use on the following surfaces:

- As applicable to waterproofing membrane being applied.

APPLICATION PROCESS

Full application instructions can be found at www.crommelin.com.au/full-instructions/

- Peel off paper backing tape to expose the self-adhesive layer before adhering to the application surface.
- Line up the centre of the self-adhesive tape with the junction and while progressively removing backing paper, press and rub tape to secure to the surface.
- Ensure no wrinkles or creases are formed. Fold back the un-adhered section of the fabric and apply the liquid membrane to the underside of the fabric and ensure it is well embedded into the membrane whilst still wet.
- Allow to dry thoroughly between coats.
- Follow all instructions of waterproofing membrane being applied.

SIZES

Reinforcing Fabric with Bond Breaker is available in 100mm x 6M.

PRECAUTIONS

- Where Reinforcing Fabric with Bond Breaker is used, drying times of waterproof membrane may be increased.

TRANSPORT AND STORAGE

- | | | | |
|--------------------|--------------------|------------------------|-------------------------|
| • Size: 100mm x 6M | • Weight: 0.04kg | • Cool and Dry Storage | • UN Number: N/A |
| • DG Class: N/A | • Flash Point: N/A | • Hazchem Code: N/A | • Poisons Schedule: N/A |

Crommelin[®] and other marks followed by ® are registered trademarks.

Any advice, recommendation, information, assistance or service provided by Crommelin[®] in relation to its products or their use is given in good faith, however is provided without responsibility or liability.

Customers need to undertake their own assessment to determine the suitability of a product for the intended use. As the performance of any product is subject to a wide variety of different surface types as well as environmental and surface-specific conditions, it is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs as required on the specific surface.

Crommelin[®] also reserves the right to update information without prior notice, to reflect ongoing research and product development.



7 Day Technical Support 1800 655 711

72 Division Street, Welshpool Western Australia 6106 T +61 8 9458 5711 F +61 8 9451 4749
service@crommelin.com.au www.crommelin.com.au