

## Unlock in one go

Couldn't be simpler









## Specifications

General Characteristics		Modes		Dual verification	
Material	Aluminum alloy	Operation mode	Manual mode	Alert	Anti-dismantling alert
Finishing	Electroplating		Auto mode		Outside forced lock alert
	Baking varnishing	System unlock mod	e General mode	,	Abnormal latch bolt alert
Color	Copper/Black		Dual verification mode		Low battery alert
Handle	Lever handle	<b>Electrical Power</b>		Networking Generate PIN code	
Mortise	Auto mortise	Power supply	4 AA batteries		Viewing access records
	C-grade lock cylinder	Battery life	10 months*	Emergency escape	Indoor fast
Fingerprint sensor	Semiconductor	Emergency chargin	g 5V power bank		opening mortise
Connection	Bluetooth	Operating Environment		Update	OTA or Batch update via
Access Solution		Temperature	-20°C~+60°C		rear interface
Outside unlocking	Fingerprint	Humidity	15%RH~93%RH	Indicator	Low battery indicator
	PIN code	Installation Requirements			Lock status indicator
	Key tag	Door thickness	38~60mm		Mute status indicator
	Mechanical key		60~90mm		System lock indicator
	Арр		90~120mm	Out	side forced lock indicator
Inside unlocking	Handle		Other range*	Voice guide	Human voice guide
	Button	Door swing	Left-in/Left-out		
	_	direction	Right-in/Right-out		
Capacity		Door type	Wooden/Copper/Security		
Fingerprint	100	Key Features			
Key tag	100	Lock	Indoor deadlock		
Master PIN code	1		System lock		
User PIN code	20	Safety	Hidden PIN code		
One-time PIN code	1	0	utside forced lock mode		

<sup>\* 10</sup> months: The laboratory data, the actual battery life will vary depending on the using scenarios.

<sup>\*</sup> Other range: Please consult our service agent or an authorized dealer.