



TECHNICAL DATA

SPC-121

RUST-OLEUM® SPECIALTY TUB & TILE TOUCH UP PAINT

DESCRIPTION AND USES

Rust-Oleum® Specialty Tub & Tile Touch-Up repairs chips, scratches, dents and defects on porcelain, ceramic, fibreglass, acrylic cast iron and steel surfaces that are subject to water exposure. It is a washable, moisture resistant finish that is ideal for use on tubs, tiles, sinks and toilets. This durable, two-component epoxy acrylic provides a nice gloss finish and is a quick and easy solution to make such surfaces look newer.

Do not use on areas exposed to temperatures over 93°C such as stove tops, constant high humidity/water immersion such as swimming pools, hot tubs, ponds or saunas, galvanised steel, or flexible plastic.

PRODUCT

SKU	DESCRIPTION (13.3 mL)
383194	White

PRODUCT APPLICATION

SURFACE PREPARATION

Remove all dirt, grease, oil, salt, and chemical contaminants by washing the surface with soap and water. Rinse with fresh water and allow to thoroughly dry. Remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy surfaces. Special precautions should be taken during surface preparation of pre-1960 painted surfaces as they may contain harmful lead. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding.

PRODUCT APPLICATION (cont.)

PAINTING CONDITIONS

Use when air and surface temperature is between 10-32°C and humidity is below 85% to ensure proper drying. Do not apply to surfaces, when heated, exceed 93°C.

APPLICATION

Mix each bottle by rolling between palms for 5 minutes. Pour all contents of part A into part B. Mix part B bottle again by rolling between palms for 5 minutes. Note: Use the product within 24 hours of mixing the two components. Apply Tub & Tile Touch-Up using even strokes. For deep scratches or chips, apply multiple layers allowing 10 minutes between coats. For best results, allow to dry for 3 days before exposing the surface to water. More than 2 coats will require additional cure time. **Do not use near open flame.**

DRY and RECOAT TIMES

Based on 21-27°C and 50% relative humidity. Allow more time at cooler temperatures. Dries to the touch in 20 minutes, to handle in 1 hour and is fully cured in 3 days.

CLEANUP

Clean up any excess product with lacquer thinner, rubbing alcohol or acetone.

WARNING! KEEP OUT OF REACH OF CHILDREN.

	TECHNICAL DATA	SPC-121
	RUST-OLEUM® SPECIALTY TUB & TILE TOUCH UP PAINT	

PHYSICAL PROPERTIES

TUB & TILE TOUCH-UP PAINT		
Resin Type		Epoxy Modified Acrylic
Pigment Type		Titanium Dioxide
Solvents		Ethylbenzene, Propylene Glycol Monomethyl Ether, Xylene
Weight	Per Gallon	10.5 lbs.
	Per Litre	1.3 kg
Solids	By Weight	61.2%
	By Volume	50.9%
Volatile Organic Compounds		<500 g/l (4.16 lbs./gal.)
Recommended Dry Film Thickness (DFT) per Coat		2.0-3.0 mils (50-75 μ)
Wet Film to Achieve DFT (unthinned material)		4.0-6.0 mils (100-150 μ)
Practical Coverage at Recommended DFT (assumes 15% material loss)		0.7-0.12 m ² /bottle (13.3 mL)
Dry Times at 21-27°C and 50% Relative Humidity	Touch	20 minutes
	Handle	1 hour
	Recoat	Allow 10 minutes between coats
Dry Heat Resistance		93°C
Shelf Life		3 years
Flash Point		26°C
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

