

Remsafe Venlock Mini

Sliding aluminium window restrictor



- ✓ Suitable for sliding aluminium windows with a window sill from 2 mm to 8 mm thick
- ✓ Easy 30-second DIY installation
- ✓ Complies with safety requirements under the *Strata Schemes Management Act 2015* (NSW)
- ✓ Child resistant release mechanism allows the window to be opened to its full extent if required

The Remsafe Venlock is supplied with:

- 1 x Drilling Jig
- 1 x Key
- 1 x Reversible Back-plate

Installation:

1. With the window in the closed position, place the drilling jig over the window sill at the restricted position. **Maximum opening should not exceed 12.5 cm at any point on the window.**
2. Mark drilling jig hole with sharp pencil.
3. Drill hole using a 6.5 mm or ¼ inch drill piece.
4. Place Remsafe Venlock over sill and push to lock.

For thicker window sills, the back-plate may be reversed to provide a 4 mm gap.

For windows where a gap of 6 mm and 8 mm is required, the back-plate may be removed and re-inserted with the packing plate on the inside.

For added security a second installation hole may be made and the Venlock installed against the window frame in the closed position.

Maintenance:

The manufacturer recommends maintenance is carried out on Remsafe products by a licensed tradesman every twelve (12) months. In addition, it is recommended that regular checks (every three to six months) are carried out by the user of each window safety device at the time of operation. Repeated force on a Remsafe Window Locks safety device may lead to general wear and tear and cause screws to become loose.

Consideration must be given to the local environment and maintenance carried out accordingly.

1. All screws must be checked to ensure they have not loosened. Loose screws must be tightened.
2. All lock components must be checked for any signs of corrosion, cracking, or loss of function. Any locks showing signs of corrosion, cracking, or loss of function must be replaced immediately.
3. All components must be checked to ensure against excessive movement. Any lock showing excessive movement must be replaced immediately.
4. If a window is able to be opened greater than 125 mm at any point a licensed tradesperson should be consulted for advice on the most appropriate window restrictor device for each window.

Warning: Window falls may result in injury or death. Falls from heights may still occur through windows with safety devices installed. To prevent falls from heights, climbable elements should be removed from below windows and children should be supervised around open windows.

NEVER LEAVE THE KEY UNATTENDED IN ANY REMSAFE WINDOW LOCKS PRODUCT.

Remsafe Window Locks offer safety solutions for all window types.

Contact us for orders and enquiries on +61 2 9453 5625, email info@remsafewindowlocks.com.au
or visit www.remsafewindowlocks.com.au