

# RUBBERGUARD 90° INTERNAL WATER PROOFING CORNER

## USED AS PART OF THE RUBBERGUARD WATERPROOFING SYSTEM

AVAILABLE SIZE: : 1pc



SCAN FOR  
DETAILS



**NOTE:** Due to updates in progress, packaging may vary.

### DESCRIPTION:

CEMIX® RUBBERGUARD 90° INTERNAL WATERPROOFING CORNER is a non-adhesive tape designed to reinforce right angled joints, over cementitious and plasterboard surfaces. It is used as part of the CEMIX® RUBBERGUARD waterproofing system.

### TYPICAL USES:

For reinforcing right angled joints in conjunction with the CEMIX® RUBBERGUARD system. Suitable for interior use.

### ADVANTAGES:

- Tear and rupture resistant
- Flexible - elastic recovery when exposed to movement

### STANDARDS:

BRANZ appraised when used as part of the the CEMIX® RUBBERGUARD waterproofing system.

### PREPARATION:

The substrate should be free of dust, grease, wax, oil, dirt, loose plaster, laitance, curing compounds, paint and all other friable materials and contaminants likely to prevent bonding.

New concrete should be left with a wood float finish and sufficiently aged as per manufacturer's recommendations.

All substrates should be structurally sound, securely fastened and properly supported to eliminate any movement that may cause cracking.

It is recommended to prime the surface with CEMIX® TILE BOND LATEX to stabilise the surface.

After priming, it is recommended to apply a neutral, cure sealant to all wall and floor junctions and joints.

### APPLICATION:

1. Apply the RUBBERGUARD 90° INTERNAL WATERPROOFING CORNER to a wetcoat of CEMIX® RUBBERGUARD waterproofing membrane.
2. Using a spatula, embed the internal corner into this wet coat, ensuring there are no large pockets of membrane nor air behind it.
3. Apply a second coat of CEMIX® RUBBERGUARD waterproofing membrane.

**Note:** On wall and floor joints, horizontal tape should overlap onto the corner by 80mm, and vertical tape should overlap onto the corner by 40mm.

### STORAGE & SHELF LIFE:

Store in a cool, dry place.

### TECHNICAL DATA:

APPLICATION TEMP.:	5°C - 30°C
--------------------	------------

### LIMITATIONS:

If your project requires Building Consent, please email [info@cemix.co.nz](mailto:info@cemix.co.nz) about the suitability of this product before use.



Scan to see  
Cemix videos

Visit Cemix's wide range of products at [www.cemix.co.nz](http://www.cemix.co.nz)

Concrete & Mortars   Repairs & Grouts   Admixtures   Decorative Sealers   Waterproofing   Tiling & Flooring



MORE THAN CONCRETE

0800 ASK CEMIX

TILING & FLOORING

Dec 2022 | Page 2

## RUBBERGUARD 90° INTERNAL WATERPROOFING CORNER

### DISCLAIMER:

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX®PRODUCTS LTD does not give any warranty expressed or implied as to suitability for any particular use. For all advice concerning the use or suitability of this product for a particular application, please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD, who will refund or replace it at no cost, in accordance with the requirements of the Consumer Guarantees Act.

### SCAN QR CODE FOR MORE PRODUCT DETAILS:



### CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061  
AUCKLAND NEW ZEALAND  
0800 ASK CEMIX | +64 09 636 1000  
WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pintrest/CemixNZ



YouTube/CemixVideos



Scan to see  
Cemix videos

Visit Cemix's wide range of products at [www.cemix.co.nz](http://www.cemix.co.nz)

Concrete & Mortars   Repairs & Grouts   Admixtures   Decorative Sealers   Waterproofing   Tiling & Flooring