Gate

-Oiled & Pre-Bled

Height (mm)

– Width (mm)

Thickness (mm)





69mm Slats

Can be installed in a right or left side configuration (as shown above). Can be easily converted to 1497mm in height by cutting 168mm from the top and bottom sections

This product has been primed with Feast Watson® This product has been primed with Feast Watson® Industrial Timber Oil. A single coat has been applied to all sides and is designed to help seal and protect your timber from moisture and UV before final topcoating. It can be topcoated with most waterbased and oil-based finishes. To fully protect your pre-oiled timber, we recommend topcoating your product as soon as possible following installation.

Step 1 - Ensure the surface is clean. If required, thoroughly scrub with an oxalic acid-based timber cleaner.

Step 2 - Allow the timber to dry and apply two coats of your chosen finish following label instructions.

Tannin Warning Tannin is a naturally occurring substance in timber which will leach the first few times it is exposed to moisture. This product has undergone a 'pre-bleeding' process to reduce excess surface tannin and minimise leaching. It is important to be aware that while the pre-bleeding process has flushed out a large proportion of the timber's has flushed out a large proportion of the timber's surface tannin, there is still a risk of the remaining tannin leaching from the product. Tannin can stain timber, paved areas and other nearby surfaces.

Warning: Do not burn off-cuts







