

# SAFETY DATA SHEET

## MONOCEL GOLD STAIN AND VARNISH

Infosafe No.: LQ8LO  
ISSUED Date : 14/12/2017  
ISSUED by: BONDALL PTY LTD

### 1. IDENTIFICATION

**GHS Product Identifier**

MONOCEL GOLD STAIN AND VARNISH

**Company Name**

BONDALL PTY LTD (ABN 27 008 734 996)

**Address**

113 Belmont Avenue Belmont  
WA 6104 Australia

**Telephone/Fax Number**

Tel: Australia: +61 (8)6272 3800 / New Zealand: 0800 474 7738  
Fax: +61 (8)9277 4068

**Emergency phone number**

+ 61400 705 773 or Poisons Information Centre: 0800 764 766

**Recommended use of the chemical and restrictions on use**

Pigmented polyurethane finish for dressed timber doors. Applied by brush, roller or spray.

### 2. HAZARD IDENTIFICATION

**GHS classification of the substance/mixture**

Classified as Hazardous according to the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001, New Zealand.  
Classified as Dangerous Goods for transport according to the New Zealand Standard NZS 5433:2012 Transport of Dangerous Goods on Land.

3.1C Flammable liquids: medium hazard

6.1E (Aspiration hazard 1) - Substance that is acutely toxic

6.3A Substance that is irritating to the skin

6.5B Substance that is a contact sensitiser

6.7B Substance that is a suspected human carcinogen

6.9A (Repeated exposure) - Substance that is toxic to human target organs or systems

9.1B Substance that is ecotoxic in the aquatic environment

9.2C Substance that is harmful in the soil environment

**Signal Word (s)**

DANGER

**Hazard Statement (s)**

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H372 Causes damage to organs central nervous system through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

H423 Harmful to the soil environment.

**Pictogram (s)**

Flame, Health hazard, Exclamation mark, Environment



#### Precautionary statement – Prevention

P102 Keep out of reach of children.  
P103 Read label before use.  
P104 Read Safety Data Sheet before use.  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/sparks/open flames/hot surfaces. – No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ventilating/lighting/equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P264 Wash contaminated skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.

#### Precautionary statement – Response

P101 If medical advice is needed, have product container or label at hand.  
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
P302+P352 IF ON SKIN: Wash with plenty of soap and water.  
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P308+P313 IF exposed or concerned: Get medical advice/attention.  
P314 Get medical advice/attention if you feel unwell.  
P331 Do NOT induce vomiting.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P362 Take off contaminated clothing and wash before reuse.  
P370+P378 In case of fire: Use carbon dioxide, dry chemical or foam. Alcohol resistant foam is preferred for extinction.  
P391 Collect spillage.

#### Precautionary statement – Storage

P403+P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

#### Precautionary statement – Disposal

P501 In the case of a substance that is in compliance with a HSNO approval other than a Part 6A (Group Standards) approval, a label must provide a description of one or more appropriate and achievable methods for the disposal of a substance in accordance with the Hazardous Substances (Disposal) Regulations 2001. This may also include any method of disposal that must be avoided. See Section 13 for disposal details.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Ingredients

| Name                                        | CAS         | Proportion |
|---------------------------------------------|-------------|------------|
| Alkyd resin (isocyanate modified)           | Proprietary | 30-60 %    |
| White Spirit                                | 64742-88-7  | 30-60 %    |
| Solvent naphtha, petroleum, light aromatic  | 64742-95-6  | 10-<30 %   |
| Distillates, petroleum, straight run middle | 64741-44-2  | <10 %      |
| Methyl ethyl ketoxime                       | 96-29-7     | <1 %       |
| Ingredients determined not to be hazardous  |             | To 100%    |

## 4. FIRST-AID MEASURES

---

### Inhalation

If inhaled, remove affected person from contaminated area. Keep at rest until recovered. If symptoms develop and/or persist seek medical attention.

### Ingestion

Do NOT induce vomiting. Wash out mouth and lips with water. Where vomiting occurs naturally have affected person place head below hip level in order to reduce risk of aspiration. Seek immediate medical attention.

### Skin

Remove all contaminated clothing immediately. Wash affected area thoroughly with soap and water. Wash contaminated clothing before reuse or discard. Seek medical attention.

### Eye contact

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing for several minutes until all contaminants are washed out completely. If symptoms develop and/or persist seek medical attention.

### First Aid Facilities

Eyewash, safety shower and normal washroom facilities.

### Advice to Doctor

Treat symptomatically.

### Other Information

For advice in an emergency, contact a Poisons Information Centre or a doctor at once. (0800 764 766)

## 5. FIRE-FIGHTING MEASURES

---

### Suitable Extinguishing Media

Use carbon dioxide, dry chemical or foam. Alcohol resistant foam is preferred. If not available normal foam can be used.

### Unsuitable Extinguishing Media

Do not use water jet.

### Hazards from Combustion Products

Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide and oxides of nitrogen.

### Specific Hazards Arising From The Chemical

Flammable liquid and vapour. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create fire or explosion hazard.

### Hazchem Code

•3Y

### Decomposition Temperature

Not available

### Precautions in connection with Fire

Fire fighters should wear full protective clothing and self-contained breathing apparatus (SCBA) operated in positive pressure mode. In case of fire the product may be violently or explosively reactive. Use water spray to disperse vapours. This product should be prevented from entering drains and watercourses.

## 6. ACCIDENTAL RELEASE MEASURES

---

### Emergency Procedures

Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations.

If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

## 7. HANDLING AND STORAGE

---

### Precautions for Safe Handling

Avoid contact with skin and eyes. Wear overalls, impervious gloves and safety glasses. Use in designated areas with local exhaust ventilation, away from sparks, flames and other ignition sources. Use approved flammable liquid storage containers in the work area. Prevent release of vapours and mists into workplace air. Keep containers tightly closed. Take precautionary measures against static discharges. Do not empty into drains. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands before eating, drinking, smoking or using the toilet facilities. Avoid exposure. Do not handle until all safety precautions have been read and understood.

### Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated area away from sources of ignition, oxidising agents, strong acids, foodstuffs, and clothing. Keep containers closed when not in use, securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. Ensure that storage conditions comply with applicable local and national regulations.

For information on the design of the storeroom, reference should be made to Australian Standard AS1940 (2017)- The storage and handling of flammable and combustible liquids.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

### Occupational exposure limit values

No exposure standards have been established for the mixture. However, over-exposure to some chemicals may result in enhancement of pre-existing adverse medical conditions and/or allergic reactions and should be kept to the least possible levels.

### Biological Limit Values

No biological limit allocated.

### Appropriate Engineering Controls

This substance is hazardous and should be used with a local exhaust ventilation system, drawing vapours away from workers' breathing zone. A flame-proof exhaust ventilation system is required. If the engineering controls are not sufficient to maintain concentrations of vapours/mists below the exposure standards, suitable respiratory protection must be worn. Refer to relevant regulations for further information concerning ventilation requirements.

Refer to AS 1940 (2017) - The storage and handling of flammable and combustible liquids and AS/NZS 60079.10.1(2009) Explosive atmospheres - Classification of areas - Explosive gas atmospheres, for further information concerning ventilation requirements.

### Respiratory Protection

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable vapor/mist filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements.

Reference should be made to Australian Standards AS/NZS 1715 (2009), Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716 (2012), Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

### Eye Protection

Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations.

Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 2 & 6 (2012) - Eye Protectors for Industrial Applications.

### Hand Protection

Wear gloves of impervious material such as laminated film or nitrile. Final choice of appropriate gloves will vary according to individual circumstances. i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations.

Reference should be made to AS/NZS 2161.1 (2016): Occupational protective gloves - Selection, use and maintenance.

### Body Protection

Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

### Other Information

No exposure standards have been established for this material, however, the TWA exposure standards for oil mist (mineral) is 5 mg/m<sup>3</sup>, STEL: 10 mg/m<sup>3</sup>). As with all chemicals, exposure should be kept to the lowest possible levels.

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

Source: Workplace Exposure Standards and Biological Exposure Indices.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

| Properties                | Description                       | Properties                             | Description               |
|---------------------------|-----------------------------------|----------------------------------------|---------------------------|
| Form                      | Liquid                            | Appearance                             | Tinted liquid             |
| Colour                    | Cedar, jarrah, golden oak, treak. | Odour                                  | Hydrocarbon solvent odour |
| Decomposition Temperature | Not available                     | Melting Point                          | Not available             |
| Boiling Point             | 145°C - 200°C                     | Solubility in Water                    | Insoluble                 |
| Specific Gravity          | 0.900                             | pH                                     | Not available             |
| Vapour Pressure           | 0.7 kpa (at 25°C)                 | Vapour Density (Air=1)                 | >1                        |
| Evaporation Rate          | <1 (n-Butyl acetate=1)            | Odour Threshold                        | Not available             |
| Radioactivity             | Not available                     | Partition Coefficient: n-octanol/water | Not available             |
| Density                   | Not available                     | Flash Point                            | 33°C (Closed cup)         |
| Flammability              | Flammable liquid.                 | Auto-Ignition Temperature              | Not available             |
| Flammable Limits - Lower  | 0.90% v/v                         | Flammable Limits - Upper               | 5.5% v/v                  |

## 10. STABILITY AND REACTIVITY

### Chemical Stability

Stable under normal conditions of handling and storage.

### Reactivity and Stability

React with incompatible materials.

### Conditions to Avoid

Heat, open flames and other sources of ignition.

### Incompatible materials

Strong oxidising agents.

### Hazardous Decomposition Products

Thermal decomposition may result in the release of toxic and/or irritating fumes, smoke and gases including: carbon dioxide and carbon monoxide.

### Possibility of hazardous reactions

Not available

### Hazardous Polymerization

Will not occur.

## 11. TOXICOLOGICAL INFORMATION

### Toxicology Information

No toxicity data available for this material.

### Ingestion

May be fatal if swallowed and enters airways. Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause severe pulmonary injury that may lead to death. May cause irritation to the mouth, throat, esophagus and stomach with symptoms of nausea, abdominal discomfort, vomiting and diarrhoea.

**Inhalation**

Inhalation of product vapours may cause irritation of the nose, throat and respiratory system.

**Skin**

Causes skin irritation. Skin contact will cause redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis. May cause an allergic skin reaction.

**Eye**

May be irritating to eyes. The symptoms may include redness, itching and tearing.

**Respiratory sensitisation**

Not expected to be a respiratory sensitiser.

**Skin Sensitisation**

May cause an allergic skin reaction.

**Germ cell mutagenicity**

Not considered to be a mutagenic hazard.

**Carcinogenicity**

Suspected of causing cancer. Classified as a suspected human carcinogen.

**Reproductive Toxicity**

Not considered to be toxic to reproduction.

**STOT-single exposure**

Not expected to cause toxicity to a specific target organ.

**STOT-repeated exposure**

Causes damage to organs central nervous system through prolonged or repeated exposure.

**Aspiration Hazard**

May be fatal if swallowed and enters airways.

## 12. ECOLOGICAL INFORMATION

---

**Ecotoxicity**

Toxic to aquatic life with long lasting effects. Harmful to the soil environment.

**Persistence and degradability**

Not available

**Mobility**

Not available

**Bioaccumulative Potential**

Not available

**Other Adverse Effects**

Not available

**Environmental Protection**

Do not discharge this material into waterways, drains and sewers.

## 13. DISPOSAL CONSIDERATIONS

---

**Disposal considerations**

Product Disposal:

Product wastes are controlled wastes and should be disposed of in accordance with all applicable local and national regulations. This product can be disposed through a licensed commercial waste collection service. In this specific case the product is a flammable substance and therefore can be sent to an approved high temperature incineration plant for disposal.

Personal protective clothing and equipment as specified in Section 8 of this SDS must be worn during handling and disposal of this product. The ventilation requirements as specified in the same section must also be followed, and the precautions given in Section 7 of this SDS regarding handling must also be followed.

Do not dispose into the sewerage system. Do not discharge into drains or watercourses or dispose where ground or surface waters

may be affected.

In New Zealand, the disposal agency or contractor must comply with the New Zealand Hazardous Substances (Disposal) Regulations 2001. Further details regarding disposal can be obtained on the EPA New Zealand website under specific group standards.

#### Container Disposal:

The container or packaging must be cleaned and rendered incapable of holding any substance. It can then be disposed of in a manner consistent with that of the substance it contained. In this instance the packaging can be disposed through a commercial waste collection service.

Alternatively, the container or packaging can be recycled if the hazardous residues have been thoroughly cleaned or rendered non-hazardous.

In New Zealand, the packaging (that may or may not hold any residual substance) that is lawfully disposed of by householders or other consumers through a public or commercial waste collection service is a means of compliance with regulations.

## 14. TRANSPORT INFORMATION

---

### Transport Information

#### Road and Rail Transport:

This material is classified as Dangerous Goods Class 3 - Flammable Liquid

Must not be loaded in the same freight container or on the same vehicle with:

- Class 1: Explosives
- Division 2.1: Flammable gases
- Division 2.3: Toxic gases
- Division 4.2: Spontaneously combustible substances
- Division 5.1: Oxidising substances
- Division 5.2: Organic peroxides or
- Class 7: Radioactive materials unless specifically exempted.

Must not be loaded with in the same freight container; and on the same vehicle must be separated horizontally by at least 3 metres unless all but one are packed in separate freight containers with:

- Division 4.3: Dangerous when wet substances

Goods of packing group II or III may be loaded in the same freight container or on the same vehicle if transported in segregation devices with:

- Division 4.2: Spontaneously combustible substances
- Division 4.3: Dangerous when wet substances
- Division 5.1: Oxidising substances
- Division 5.2: Organic peroxides

#### Marine Transport (IMO/IMDG):

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Class/Division: 3

UN No: 1263

Proper Shipping Name: PAINT SOLVENT NAPHTHA, PETROLEUM, MEDIUM ALIPHATIC (MARINE POLLUTANT)

Packing Group: III

EMS: F-E, S-E

Special Provisions: 163, 223, 367, 955

#### Air Transport (ICAO/IATA):

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

Class/Division: 3

UN No: 1263

Proper Shipping Name: Paint

Packing Group: III

Packaging Instructions (passenger & cargo): 355

Packaging Instructions (cargo only): 366

Hazard Label: Flammable liquid

Special Provisions: A3, A72, A192

**U.N. Number**

1263

**UN proper shipping name**

PAINT

**Transport hazard class(es)**

3

**Packing Group**

III

**Hazchem Code**

•3Y

**IERG Number**

14

**IMDG Marine pollutant**

Yes

**Transport in Bulk**

Not available

**Special Precautions for User**

Not available

## 15. REGULATORY INFORMATION

---

**Regulatory information**

Classified as Hazardous according to the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001, New Zealand.

Group Standard: Surface Coatings and Colourants (Flammable, Toxic [6.7]) Group Standard 2006

**HSNO Approval Number**

HSR002669

## 16. OTHER INFORMATION

---

**Date of preparation or last revision of SDS**

SDS created: December 2017

**References**

- Workplace Exposure Standards and Biological Exposure Indices.
- Transport of Dangerous goods on land NZS 5433.
- Preparation of Safety Data Sheets - Approved Code of Practice Under the HSNO Act 1996 (HSNO CoP 8-1 09-06).
- Assigning a hazardous substance to a group standard.
- American Conference of Industrial Hygienists (ACGIH).

**Contact Person/Point**

Chemist: Tel No: (08) 6272-3800

Emergency: Tel No: 0438 916 539

## END OF SDS

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

The compilation of SDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any SDS displayed is permitted for personal use only and otherwise is not permitted. In particular the SDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of SDS without the express written consent of Chemical Safety International Pty Ltd.