

# Retract Away Clothes Lines



## Clothes lines that extend up to 8 or 10m

A discreet clothes line suitable for long, narrow areas. Lines may be retracted into the cabinet when not in use.

### Features and Benefits

Aesthetically discreet

5 lines with wide spacing

Easy DIY installation


Min. distance 2m

Max. distance 8m or 10m

### Colours

- Surfmist
- Classic Cream
- Woodland Grey
- Monument

### Mounting Options



Wall to Wall



Wall to Post



Post to Wall



Post to Post

1 x Retract Away 40 or 50 Cabinet	1 x Retract Away 40 or 50 Cabinet	1 x Retract Away 40 or 50 Cabinet	1 x Retract Away 40 or 50 Cabinet
-	1 x Post (standard or plated)	1 x Mounting Bar	1 x Mounting Bar
-	1 x Socket (optional)	1 x Post (standard or plated)	2 x Posts (standard or plated)
-	-	1 x Socket (optional)	1 x Socket (optional)*

When fixing to alternative surfaces such as weatherboard, fibro, blueboard etc. fix directly to the stud – alternatively support battens should be used

For Post to Post installations with one removable post, the Retract Away is preferably fitted to the fixed Post

Ground Socket is only required if Post is to be removable



Surfmist model shown

## Retract Away 40

A discreet clothesline extending from 2 – 8m.

100% Australian made using Australian materials and labour

May be installed from a minimum of 2m to a maximum of 8m

May be installed wall to wall, wall to post, post to wall or post to post

5 lines are 150mm apart and offer up to 40m line space

Cord will flex through centre (refer to instructions to ensure correct height installation)

Assembled dimensions: 820mm x 125mm x 170mm

Carton dimensions: 840mm x 190mm x 130mm

### Retract Away 40

Colour	Fineline	APN	VPN
Surfmist	0225242	9315384001767	RA40SM
Classic Cream	4510551	9315384000258	RA40CC
Woodland Grey	4510550	9315384000241	RA40WG
Monument	0225243	9315384001804	RA40MON

### Compatible Products

Mounting Options	See page
Retract Away Post (for soil installations)	20
Retract Away Post Plated (for hard surface installations)	20
Retract Away Mount Bar	20
Ground Socket	20



Number of People



Line Space



Area Required



Cabinet Size



Weight



Number of Lines



Available Separately



Available Separately



Surfmist model shown

## Retract Away 50

A discreet clothesline that extends from 2 – 10m.

100% Australian made using Australian materials and labour

May be installed from a minimum of 2m to a maximum of 10m

May be installed wall to wall, wall to post, post to wall or post to post

5 lines are 150mm apart and offer up to 50m line space

Cord will flex through centre (refer to instructions to ensure correct height installation)

Assembled dimensions: 820mm x 125mm x 170mm

Carton dimensions: 840mm x 190mm x 130mm

### Retract Away 50


Colour	Fineline	APN	VPN
Surfmist	0225244	9315384001774	RA50SM
Classic Cream	4510554	9315384000272	RA50CC
Woodland Grey	4510553	9315384000265	RA50WG
Monument	0225245	9315384001811	RA50MON

### Compatible Products

Mounting Options	See page
Retract Away Post (for soil installations)	20
Retract Away Post Plated (for hard surface installations)	20
Retract Away Mount Bar	20
Ground Socket	20



Number of People



Line Space



Area Required



Cabinet Size



Weight



Number of Lines



Available Separately



Available Separately

# Retract Away Accessories

## Retract Away Post

For soil installations

Post dimensions: 2300mmH x 50mmW x 50mmD

Fixing height: Embed to required depth

Refer to Installation Instructions for concrete footing details

Colour	Fineline	APN	VPN
Surfmist	0225246	9315384001781	RAPOSTSM
Classic Cream	4510556	9315384000296	RAPOSTCC
Woodland Grey	4510555	9315384000289	RAPOSTWG
Monument	0225247	9315384001828	RAPOSTMON

## Retract Away Post Plated

For hard surface installations

Post dimensions: 1915mmH x 50mmW x 50mmD

Plate dimensions: 6mmH x 100mmW x 150mmD

Fixing height: 1880mm

Colour	Fineline	APN	VPN
Surfmist	0225249	9315384001842	RAPOSTPLSM
Classic Cream	4510558	9315384000319	RAPOSTPLCC
Woodland Grey	4510557	9315384000302	RAPOSTPLWG
Monument	0225250	9315384001859	RAPOSTPLMON

## Retract Away Mount Bar

Mount bar dimensions: 25mmH x 823mmW x 25mmD

Inner fixing points: 35mm centre to centre

Outer fixing points: 783mm centre to centre

Colour	Fineline	APN	VPN
Surfmist	0225251	9315384001798	RAMBARSM
Classic Cream	4510561	9315384000333	RAMBARCC
Woodland Grey	4510559	9315384000326	RAMBARWG
Monument	0225252	9315384001835	RAMBARMON

## Ground Socket

External dimensions: 460mmH x 88mmW x 88mmD

Internal dimensions: Suits 50x50mm square or 57mm round tube

Colour	Fineline	APN	VPN
Black	4514213	9315384400089	GSKT



Retract Away Post



Retract Away Plated Post



Retract Away Mount Bar



Ground Socket

# Retract Away Mounting Options

## Mounting Options at a glance



**Wall to Wall**

1 x Retract Away  
40 or 50 Cabinet

-

-

-



**Wall to Post**

1 x Retract Away  
40 or 50 Cabinet

-

1 x Post

1 x Socket (optional)



**Post to Wall**

1 x Retract Away  
40 or 50 Cabinet

1 x Mounting Bar

1 x Post

1 x Socket (optional)



**Post to Post**

1 x Retract Away  
40 or 50 Cabinet

1 x Mounting Bar

2 x Posts

1 x Socket (optional)

## Wall to Wall


**Products required:** 1x Retract Away 40 or 50 Cabinet

**Fixings supplied:** Cabinet: Catch (Hook), 2x 25mm ZP washers

**You will require:** For masonry walls: 4x M8x75mm coach screws, 4x 10x75mm wall plugs, safety glasses, hammer drill and 10mm masonry bit

For timber walls: 4x M8x75mm coach screws, drill and 5mm bit

**Also required:** 2x 13mm spanners/sockets, spirit level, tape measure, knife and pencil



**Wall to Wall**

## Wall to Post

**Products required:** 1x Retract Away 40 or 50 Cabinet, 1x Post, Ground Socket optional

**Fixings supplied:** Cabinet: Catch (Hook), 2x 25mm ZP washers  
Post: 2x M8x65mm bolts and 2x M8 nuts

**You will require:** For masonry walls: 2x M8x75mm coach screws, 2x 10x75mm wall plugs, safety glasses, hammer drill and 10mm masonry bit


For timber walls: 2x M8x75mm coach screws, drill and 5mm bit

**In-ground Post:** concrete mix, drainage gravel, shovel and bucket

**Plated Post:** 4x M6 Galvanised masonry screws/screw bolts (min. embedment 45mm), 4x M6 Galvanised washers, safety glasses, hammer drill, 6mm masonry bit, 2x 10mm spanners/sockets.

Note: For larger M8 fixings use 8mm masonry bit and 13mm spanners. Refer to Manufacturer's TDS (Technical Data Specifications) for further information

**Also required:** 2x 13mm spanners/sockets, spirit level, tape measure, knife and pencil



**Wall to Post**

# Retract Away Mounting Options (cont.)



Post to Wall

## Post to Wall

**Products required:** 1x Retract Away 40 or 50 Cabinet, 1x Post, 1x Mounting Bar, Ground Socket optional

**Fixings supplied:** **Cabinet:** Catch (Hook), 2x 25mm ZP washers  
**Post:** 2x M8x65mm bolts and 2x M8 nuts  
**Mounting Bar:** 2x M8x90mm bolts, 2x M8x40mm bolts, 4x M8x19mm washers, 4x M8 nuts

**You will require:** **Masonry walls:** 2x M8x75mm coach screws, 2x 10x75mm wall plugs, safety glasses, hammer drill and 10mm masonry bit

**Timber walls:** 2x M8x75mm coach screws, drill and 5mm bit

**In-ground Post:** concrete mix, drainage gravel, shovel and bucket

**Plated Post:** 4x M6 Galvanised masonry screws/screw bolts (min. embedment 45mm), 4x M6 Galvanised washers, safety glasses, hammer drill, 6mm masonry bit, 2x 10mm spanners/sockets.

Note: For larger M8 fixings use 8mm masonry bit and 13mm spanners. Refer to Manufacturer's TDS (Technical Data Specifications) for further information

**Also required:** 2x 13mm spanners/sockets, spirit level, tape measure, knife and pencil



Post to Post

## Post to Post

**Products required:** 1x Retract Away 40 or 50 Cabinet, 2x Posts, 1x Mounting Bar, Ground Socket optional

**Fixings supplied:** **Cabinet:** Catch (Hook), 2x 25mm ZP washers  
**Each Post:** 2x M8x65mm bolts and 2x M8 nuts  
**Mounting Bar:** 2x M8x90mm bolts, 2x M8x40mm bolts, 4x M8x19mm washers, 4x M8 nuts

**You will require:** **In-ground Posts:** concrete mix, drainage gravel, shovel and bucket

**Plated Posts:** 8x M6 Galvanised masonry screws/screw bolts (min. embedment 45mm), 8x M6 Galvanised washers, safety glasses, hammer drill, 6mm masonry bit, 2x 10mm spanners/sockets.

Note: For larger M8 fixings use 8mm masonry bit and 13mm spanners. Refer to Manufacturer's TDS (Technical Data Specifications) for further information

**Also required:** 2x 13mm spanners/sockets, spirit level, tape measure, knife and pencil