

Makita[®]

18V Caulking Gun

DCG180



Setup Options

Model No.	Image	Barcode	Description
DCG180Z		0088381658645	18V CAULKING GUN 300ML
DCG180ZB		0088381658652	18V CAULKING GUN 600ML

Product Objectives

- The 18V Caulk and Adhesive is a versatile, powerful, and lightweight solution for any tradesman dispensing large amounts of caulk and adhesives.
- The DCG180 delivers 5,000N. of dispensing force for even the highest viscosity adhesives and sealants. The DCG180 features a 5-speed dial with 0-28mm per second, and a variable speed trigger that allows the user to optimise the flow rate according to the application.



Product Overview

360 degree rotating holder

Overload indicator lamp

Anti-drip function

Variable speed control dial

LED job light



Product Specification Sheet



	DCG180	DCG180B
Cartridge size	300mm	600ml
Max. pushing force	5,000N	
Compatible sealant size	Ø51.0 x 215mm	
Compatible sealant type	Cartridge,	Sausage pack, Bulk sealant
No load speed	0 - 28mm/sec	
Overall length	404mm / 538mm	
Skin weight	2.1kg	
Weight (with battery)	2.7kg	
Voltage	18V	

- **360 degree rotating holder** - Even in caulking hard to reach places, you can avoid awkward working postures by simply rotating sealant holder so that the angle of the cartridge nozzle fits over the gap to caulk.
- **Anti-drip function** – stops excess sealant from oozing out just upon release of the switch trigger by removing the residual pressure inside of sealant cartridge/holder.
- **LED job light** – illuminates working area with pre-glow and after glow
- **Overload indicator lamp** – Single LED light indicates how heavily the machine is loaded for preventing breakage of the sealant cartridge. Blinking light indicates the machine is nearly overloaded. Solid light indicates the machine is overloaded and the overload circuit will shut off the power.
- **Variable speed control dial** – by dial and trigger for maximum control over the sealant flow rate. Speed control dial, enables to set maximum pushing speed for optimum sealant flow rate to match the material of workpiece or the width of the gap to caulking. Variable speed trigger switch, allows for fine adjustment of pushing speed for controlled sealant flow rate at startup and around the corner.

Advantages

Power



Makita Built motor delivers 5,000N dispensing force

Versatility



Variable speed dial and trigger optimizes flow rate from 0-28mm per second

Ergonomics



360 degree rotating holder for access to hard to reach places

Convenience



Built in LED with afterglow illuminates the work area


Accessories



Standard Accessories – DCG180

 A black plastic holder set for a 300mL cartridge, including the main holder, a mixing cap, and a mixing rod.	196351-8	300mL Holder Set Complete
------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------	---------------------------

Standard Accessories – DCG180B

 A silver plastic holder set for a 600mL cartridge, including the main holder, a mixing cap, a mixing rod, and three teal mixing tips.	196352-6	600mL Holder Set Complete
---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------	---------------------------