



# CARPET ADHESIVE

## READY TO USE ADHESIVE FOR MOST CARPETS

AVAILABLE SIZE: 1L, 2L, 4L



SCAN FOR  
DETAILS



WATER  
WASHUP



NON  
FLAMEABLE



ECO  
FRIENDLY



SERVICE  
TIME

**NOTE:** Due to updates in progress, packaging may vary.

### DESCRIPTION:

CEMIX® CARPET ADHESIVE is a ready to use adhesive, designed for the installation of carpets onto a variety of substrates.

### TYPICAL USES:

CEMIX® CARPET ADHESIVE can be used on concrete, cement renders, screeds, fibrous cement sheeting and timber. Suitable for use in interior floor applications in a domestic and commercial environment.

### ADVANTAGES:

- High initial grab
- Non-flammable
- Eco-friendly
- Mould resistant

### YIELD:

FLOOR COVERING	TROWEL SIZE	COVERAGE
SMOOTH BACKED CARPET	2.4mm V notch trowels	4m <sup>2</sup> per L
TEXTURE BACKED CARPET	3.2mm V notch trowels	3m <sup>2</sup> per L
FOAM/FIBRE BACKED CARPET	1.6mm V notch trowels	5m <sup>2</sup> per L

### PREPARATION:

The substrate should be free of dust, grease, wax, oil, dirt, loose plaster, laitance, curing compounds, paint and all other friable materials and contaminants likely to prevent the adhesive bonding.

New concrete should be left with a wood float finish and sufficiently aged as per manufacturer's recommendations.

All substrates should be structurally sound, securely fastened

and properly supported to eliminate any movement that may cause cracking.

CEMIX® screeds, floor levellers and plasters must be allowed to cure.

It is recommended to prime the surface with a CEMIX® bonding agent before the application of CEMIX® CARPET ADHESIVE.

### MIXING:

No mixing required.

### APPLICATION:

1. Stir before use.
2. Spread the adhesive on the substrate with a V notched trowel. The adhesive must be tacky before the carpet is placed onto the substrate.

To check if the adhesive is tacky, place a small piece of carpet onto the adhesive, and then pull away. If there are visible strings of adhesive, then the adhesive is tacky.

### DRYING & CURING:

Once the carpet has been laid, they must not be trafficked upon or disturbed for a minimum of 24 hours at 20°C. If application is over a non-porous substrate, allow for a minimum of 48 hours at 20°C. Note that the cure time will be delayed if the temperature is below 20°C and/or there is insufficient air circulation.

### CLEANING:

Clean tools with water immediately after use.



Scan to see  
Cemix videos

Visit Cemix's wide range of products at [www.cemix.co.nz](http://www.cemix.co.nz)

Concrete & Mortars

Repairs & Grouts

Admixtures

Decorative Sealers

Waterproofing

Tiling & Flooring

# CARPET ADHESIVE

## STORAGE & SHELF LIFE:

Up to 12 months when stored in the original, unopened packaging, in a dry place at 23°C and 50% relative humidity.

## LIMITATIONS:

Not suitable for exterior use. Not suitable for use in water immersion applications i.e. showers, baths, swimming pools and spas etc.

If your project requires Building Consent, please email [info@cemix.co.nz](mailto:info@cemix.co.nz) about the suitability of this product before use.

**Read label before use. Keep out of reach of children.**  
**If medical advice is needed, have product container or label at hand.**

**DANGER**



## HAZARD STATEMENTS:

Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction.

## SAFETY INSTRUCTIONS:

Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing mist/vapours/spray. Contaminated work clothing should not be allowed out of the workplace.

## RESPONSE:

**IIF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. Take off contaminated clothing and wash before reuse. **IF ON SKIN:** Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention.

## INGREDIENTS:

rosin-colophony, CAS: 8050-09-7, 6-10%  
limestone, CAS: 1317-65-3, 20-40%  
acrylic copolymer, proprietary, CAS: NA, 35-50%  
naphtha petroleum, heavy, hydrotreated CAS: 64742-48-9, 3-5%  
proprietary ingredients CAS: NA, 2-5%  
water CAS: 7732-18-5, 22-26%

## DISCLAIMER:

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this products packaging, CEMIX® PRODUCTS LTD does not give any warranty express or implied as to its suitability for any particular use. For all advice concerning the use of, or suitability of this product for a particular application please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD who will refund or replace it in accordance with the requirements of the Consumer Guarantees Act.

## SCAN QR CODE FOR MORE PRODUCT INFORMATION



## CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061  
AUCKLAND NEW ZEALAND  
0800 ASK CEMIX | +64 09 636 1000  
[WWW.CEMIX.CO.NZ](http://WWW.CEMIX.CO.NZ)



Twitter/CemixNZ



Facebook/CemixNz



Pinterest/CemixNZ



YouTube/CemixVideos



Scan to see  
Cemix videos

Visit Cemix's wide range of products at [www.cemix.co.nz](http://www.cemix.co.nz)

Concrete & Mortars   Repairs & Grouts   Admixtures   Decorative Sealers   Waterproofing   Tiling & Flooring