



WET AREA WATERPROOFING

SINGLE COMPONENT UNDERTILE | INDOOR/OUTDOOR | COMPLIES WITH AS4858

DESCRIPTION

Bastion Wet Area Waterproofing is an effective and simple to use waterproofing membrane designed to waterproof under tiles. It can be applied using a normal brush or roller.

SUITABLE SUBSTRATES

Wet area grade plasterboard, fibre-cement, marine plywood, concrete, sand/cement renders and screeds (cured for at least 7 days), bricks, AAC blocks.

MINIMUM AREAS RECOMMENDED TO WATERPROOF

Bathroom: Full shower recess floor, over hob and 100mm onto bathroom floor. Up recess walls 150mm and 1800mm up internal vertical corner of recess. Check your local government requirement.

Balcony: Full deck, minimum 100mm up wall(s) and over and down edge(s).

SURFACE PREPARATION

Ensure surfaces are sound and dry and floor sheeting materials are installed to manufacturer's instructions. Remove all contaminating materials such as dust, oil, paint and curing compounds. Treat all cracks and floor/wall junctions with a neutral cure silicone.

PRIMING

Prime all areas to be waterproofed with Bastion Multipurpose Primer according to the instructions on the packaging.

APPLICATION

1. Apply first coat of Bastion Wet Area Waterproofing with a clean paint brush or roller so that all the surfaces (wall and/or floor) are fully covered.
2. While the first coat is still wet, install Bastion Reinforcing Mat in all wall/floor junctions, cracks and over the shower hob.
3. Remove any wrinkles in the mat and immediately apply a second coat. In areas where no mat has been used, allow 4 hours drying time before applying the second coat.
4. The membrane should be minimum 1.0mm (on floors) or 0.5mm (on walls) thick after 2 coats.

COVERAGE

12.5kg of Bastion Wet Area Waterproofing will waterproof up to approximately 10m² on walls and 4.5 m² on floors, based on 2 coats. Coverage will vary depending on method of application.

DRYING TIME

Recoat once first coat is totally dry (approx. 4 hours at 23°C). When Bastion Reinforcing Mat is used, the second coat can be applied immediately after the mat has been bedded into the first wet coat. Do not commence tiling before the membrane is completely dry. This can take up to 48 hours or up to 72 hours where membrane is applied over a bond breaker. Drying time will always depend on temperature and humidity.

CLEANING

Wash brushes, sponges and rollers with clean water whilst still wet.

COMPATIBLE ADHESIVES

Bastion Mastic Powder Adhesive

Bastion Premixed Tile Adhesive *With porous tiles only

Dunlop Tiler's Mastic

Dunlop Tiler's Rubber Modified Tile Adhesive

Dunlop Universal Tile Adhesive

SAFETY DATA

This product causes skin irritation and serious eye irritation. May cause damage to organs through prolonged or repeated exposure. Suspected of causing genetic defects. May cause cancer. In case of contact with the eyes rinse with running water until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Wear protective gloves, clothing, eye and face protection. Avoid inhaling fumes/gas/mist/vapours/spray. Ensure adequate ventilation during mixing and application. Store locked up. Check with your local Council regarding the disposal of contents. Keep out of the reach of children. Call the Poisons Information Centre on 131 126 (AUS) and 0800 764 766 (NZ) or call a doctor if you feel unwell. At times updates can occur to data. For additional information and to ensure you have the most current technical and safety information please consult the latest safety data sheets (SDS) found on the product page at www.bunnings.com.au

PACKAGING SIZE

Available in a 12.5kg bucket.

DISCLAIMER

The technical details, recommendations and other information contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our products are used and handled correctly and in accordance with any applicable Australian Standards. Our instructions and recommendations are only for the uses they are intended. Users are advised to confirm that this product is suitable for their application and conforms with the specifications of the system being employed and other products in that system. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program. Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may affect specific installation recommendations. The supply of our products and services is also subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are otherwise available to you on request. You should make yourself familiar with them.

CONTACT DETAILS

Bunnings Pty Ltd

Botanicca 3,

570 Swan Street,

Richmond, VIC 3121

(03) 8831 9777

