

# POLYPRO

## PROFESSIONAL SLAB UNDERLAY

**MEDIUM  
IMPACT &  
HIGH IMPACT**

Builders film is manufactured to comply with the requirements of Australian Standard 2870.

### Product applications

- Concrete underlay
- Moisture barrier
- Covering equipment
- Landscaping
- Protection sheet



Polyethylene film using recycled resins or virgin low density polyethylene resins. Suited for use as a damp proof membrane or vapour barrier. 200um gauge for medium or high impact resistance uses.

# POLYPRO

## PROFESSIONAL SLAB UNDERLAY



### Application

Slab onground construction requires that a branded concrete underlay or vapour barrier is used to prevent moisture vapour or groundwater penetration into the concrete slab. AS/NZS 2870 requires that such products meet a minimum requirement of thickness and strength.

**CAgroup offers both Medium and High Impact Concrete Underlay.**

CAgroup products are recognised for their quality and compliance with both Australian standards (AS 2870 and AS2904) and the Builders Code of Australia (BCA).

**Vapour Barriers and Damp-Proofing membranes are required to conform to:**

- Material type – must be polyethylene
- Continuous branding – the manufacturer's and distributor's name, trademark or code;
- Film thickness – in accordance with AS/NZS4347.9
- Medium Impact resistance – in accordance with AS4347.6
- High Impact resistance – in accordance with AS4347.6
- Puncture and Moisture penetration.

### Industrial Film

Industrial film products are produced in varying widths, thicknesses and colours. There are a wide variety of industries and applications using high quality CA Group Industrial Building Films.

CAgroup offers all types of industrial film, including – Black, Orange, Natural and Handy Rolls