



Ready-to-Go

COLOURED GROUT

DUNLOP Ready-to-Go COLOURED GROUT is a ready-mixed, easy to apply grout that is suitable for walls and floors in indoor and outdoor* situations. DUNLOP Ready-to-Go COLOURED GROUT can be used in tile joints between 1mm and 5mm wide. When rejuvenating old grout on walls ensure a minimum of 1mm and on floors a minimum 2mm depth. This product contains Grout Shield which is a powerful mould and bacteria growth inhibitor to keep surfaces looking better for longer.



JOINT PREPARATION

Ensure joints are clean and free from excess adhesive. The depth of the grout joint should be at least half its width. Remove all tile spacers and do not grout until the tiling has set firmly.

APPLICATION

1. Prior to grouting, it is advisable to check the ease of cleaning from the face of the tile being used.
2. Cut the tapered nozzle so that the opening of the nozzle is as wide as necessary for your project. Reseal the nozzle and holding the bottle upside down, shake for 15 seconds.
3. Squeeze grout out of bottle and apply the grout into the joints whilst holding the bottle at a 90° angle to the surface being grouted.
4. Ensure that the grout has been compacted firmly into the joint using a grout float or squeegee.
5. Minimise any excess grout from the surface of the tile by scraping with grout float or squeegee. Allow the grout to firm up in the joint for approximately 15 min.
6. Remove excess grout from the surface of the tiles with a dense, damp, small-pored sponge working diagonally across the joint. Rinse the sponge frequently in clean water. Use a minimum amount of water when cleaning the tile surface and smoothing the joints so as to minimise water float shade variation and shrinkage.
7. When DUNLOP Ready-To-Go COLOURED GROUT has sufficiently hardened in the tile joints and is touch dry (approx. 6-24 hrs) buff and polish the tile surface with a clean dry cloth.
8. *When grouting outdoors, it is essential to protect the grouted area from all extremes of climate until the grout has reached full cure which is 7 days.

COVERAGE

The table below shows approximate coverage (square metres) per 800g bottle. Allow an extra 10-15% for wastage due to application technique, tile types and job site variations.

Tile Size (LxWxD)	1.5mm	3mm	5mm
25x25x4	1.04m ²	0.52m ²	0.31m ²
100x100x8	2.08m ²	1.04m ²	0.63m ²
200x200x8	4.17m ²	2.08m ²	1.25m ²
330x330x9	6.11m ²	3.05m ²	1.83m ²

DRYING TIME

Initial set is after 24 hours at 23°C and 50% relative humidity after which shower walls can be exposed to water. Shower floors can be used after 3 days. The grout will reach full cure after 7 days. Allow longer for lower temperatures, dense tiles or high relative humidity.

CLEANING

All tools should be cleaned with water immediately after use.

SHELF LIFE

12 months when stored in the original unopened packaging, in a dry place at 23°C and 50% relative humidity.

PRECAUTIONS

Do not use in expansion or movement joints, use DUNLOP COLOURED SILICONE. Not suitable for use in immersed situations such as swimming pools. Instead, use DUNLOP Flexible Coloured Grout White mixed with undiluted DUNLOP PRIMER AND ADDITIVE. Depending on application technique, some concavity may occur in wider joints. Seal with DUNLOP GROUT SEALER, not suitable with a solvent-based sealer. Clean regularly with DUNLOP TILE & GROUT CLEANER to keep your surfaces looking better for longer. Please refer to the Safety Data Sheet for additional information on substrate preparation.



Ready-to-Go

COLOURED GROUT

SAFETY

Causes skin irritation, serious eye damage and may cause respiratory irritation. Suspected at causing genetic defects and may cause cancer. Harmful to aquatic life with lasting effects. Avoid contact with skin and eyes; in case of contact with the eyes, wash out immediately with fresh running water. If irritation continues, seek medical attention. Wear protective gloves, clothing, face and eye protection. Avoid inhaling dust/fumes/gas/mist/vapours/spray. Ensure adequate ventilation during mixing and application. Check with your local Council regarding the disposal of contents, dispose of packaging thoughtfully and recycle where possible. Keep out of the reach of children. Call the Poisons Information Centre on 131 126 (AUS) and 0800 764 766 (NZ) or call a doctor if you feel unwell. Additional information is in the Safety Data Sheet (SDS). At times updates can occur to data, please ensure you have the most current Technical Data Sheets and SDS information found at www.dunlopbuildingproducts.com.

TECHNICAL DATA

PRODUCT IDENTITY	
Form:	Soft Paste
Colour:	Ultrawhite, White, Buff, Travertine, Misty Grey, Magellan Grey, Slate Grey, Charred Ash, Jet Black
Size:	800g, 1.5kg (Ultrawhite ONLY)
APPLICATION PROPERTIES	
Mixing Ratio	No mixing required
Working Time:	15-30 minutes (25°C and 50% relative humidity)

DISCLAIMER

The technical details, recommendations and other information contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our products are used and handled correctly and in accordance with any applicable Australian Standards. Our instructions and recommendations are only for the uses they are intended. Users are advised to confirm that this product is suitable for their application and conforms with the specifications of the system being employed and other products in that system. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program. Country specific recommendations, depending on local standards, codes of practice, building regulations

or industry guidelines, may affect specific installation recommendations. The supply of our products and services is also subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are otherwise available to you on request. You should make yourself familiar with them.

This datasheet was issued in August 2022 and is valid for 3 years, unless updated sooner. Always refer to www.dunlopbuildingproducts.com for the latest technical data from ARDEX Australia Pty Ltd.