



MORE THAN CONCRETE

0800 ASK CEMIX

TILING & FLOORING

Dec 2022 | Page 1



TILING SEALANT

COLOURED SILICONE

AVAILABLE SIZE: : 310ml



SCAN FOR
DETAILS

NOTE: Due to updates in progress, packaging may vary.

DESCRIPTION:

CEMIX® TILING SEALANT is a flexible, coloured silicone, designed to seal and waterproof joint areas.

TYPICAL USES:

CEMIX® TILING SEALANT can be used in interior and exterior applications, for sealing and waterproofing joints between a variety of surfaces, including tiles, glass, enamel, aluminium, granite, porcelain and sanitary acrylics.

PREPARATION:

The substrate should be free of dust, grease, wax, oil, dirt, loose plaster, laitance, curing compounds, paint and all other friable materials and contaminants likely to prevent bonding.

The substrate should be dry.

MIXING:

No mixing required.

APPLICATION:

1. Trim the end of the nozzle to the correct bead width.
2. Place the cartridge in the applicator gun.
3. Apply the product in a steady continuous bead, ensuring good contact with both sides of the joint.
4. Remove any excess product with a spatula.
5. Clean off any product residue with white spirits and a blade.

Apply product at a temperature between 5 °C and 35 °C.

Note: CEMIX® TILING SEALANT can be used for a maximum joint depth of 15mm. Use a backing rod for joints deeper than 10mm.

DRYING & CURING:

Skin forming time is 10 minutes.

CLEANING:

Clean tools with white spirits immediately after use.

STORAGE & SHELF LIFE:

24 months when stored in the original, unopened packaging, in a dry place at 23 °C and 50% relative humidity.

LIMITATIONS:

Not suitable for use under waterproofing membranes. Not suitable for use in continuous water immersion applications i.e. swimming pools and spas etc. Not suitable for mirror backed tiles and mirrors including mirror backed splashbacks. Not suitable to be painted over.

Contact with natural stone, bitumen-based materials and rubber modified adhesives and metals such as brass and copper, may cause discolouration.

If your project requires Building Consent, please email info@cemix.co.nz about the suitability of this product before use.

Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

DANGER



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring



MORE THAN CONCRETE

TILING SEALANT

HAZARD STATEMENTS:

Causes mild skin irritation. Causes serious eye damage.

SAFETY INSTRUCTIONS:

Wear protective gloves/protective clothing/eye protection/face protection.

RESPONSE:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor/physician/first aider. If skin irritation occurs: Get medical advice/attention.

INGREDIENTS:

Ethyltriacetoxysilane, CAS: 17689-77-9, <5%
Polydimethylsiloxane, CAS: 63148-62-9, NotSpec.;
Fillers, CAS: NA, NotSpec.;
Auxillary substances, CAS:NA, NotSpec.

DISCLAIMER:

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX® PRODUCTS LTD does not give any warranty expressed or implied as to suitability for any particular use. For all advice concerning the use or suitability of this product for a particular application, please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD, who will refund or replace it at no cost, in accordance with the requirements of the Consumer Guarantees Act.

SCAN QR CODE FOR MORE PRODUCT DETAILS:



CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061
AUCKLAND NEW ZEALAND
0800 ASK CEMIX | +64 09 636 1000
WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pintrest/CemixNZ



YouTube/CemixVideos



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring