

AUSTRALIAN MADE



SharkBite® fittings and pipe are manufactured in Australia by Reliance Worldwide Corporation (Aust.) Pty. Ltd. in state of the art facilities. Stringent quality control and advanced manufacturing procedures guarantee product satisfaction.

25 YEAR WARRANTY⁽²⁾



The SharkBite® range of fittings and PEX pipe can be relied upon to perform year after year. SharkBite® is backed by the Reliance Worldwide Corporation (Aust.) Pty. Ltd. 25 year warranty.

VERSATILE AND REUSABLE



Can be easily disconnected using the SharkBite® Disassembly Clip. Fittings can be rotated once installed, allowing for a more versatile, easier use, especially in confined spaces. This feature is particularly useful where repairs and or maintenance are required.

QUICK AND EASY



SharkBite® is quick and easy to install, making it the most time effective plumbing system available, allowing the installer to move onto the next job faster than ever before.

Utilising state of the art push-to-connect design, DR brass fittings, the SharkBite® system is easily assembled by hand.

SHARKBITE® SYSTEM CONVERSION



SharkBite® offers a range of conversion fittings that adapt to existing SDR 7.4, SDR 9, Polybutylene and Copper piping systems.

STANDARDS APPROVED



SharkBite® fittings and pipe are Watermark approved and comply with Australian Standards.

SHARKBITE®

PLUMBING SYSTEM

SharkBite® has established a reputation as the world's #1 push-to-connect plumbing system.

- Quick and easy to use
- Fittings for PEX and Copper Pipe
- Conversion Fittings to other pipe systems
- Assemble by hand, no costly tools
- For use on hot and cold water
- Approved for behind walls and in ground⁽¹⁾
- Can be disconnected and reconnected
- Australian made
- 25 year warranty⁽²⁾
- For a copy of the Technical Manual, refer to the SharkBite® website
- Made from lead free dezincification resistant brass⁽³⁾

⁽¹⁾ Buried in ground fittings must be wrapped using Silicone Wrap.

⁽²⁾ See our website for further information on SharkBite® warranty.

⁽³⁾ Compliant with the low lead requirements specified in NSF/ANSI/CAN 372

Contents of this brochure are subject to change, please visit our website for the most up-to-date product information.



THE ORIGINAL PUSH-TO-CONNECT

☎ 1800 810 803 ✉ sales.au@rwc.com

🌐 sharkbite.com.au 📘 sharkbite.au

📷 sharkbite.au

27-28 Chapman Place
Eagle Farm QLD 4009, Australia



Reliance Worldwide Corporation (Aust) Pty. Ltd.
ABN 71 004 784 301 | AU-SB-MN0813R1



THE ORIGINAL PUSH-TO-CONNECT

NOTHING BEATS THE SHARK



CUT.
PUSH.
DONE.

Available at
BUNNINGS
warehouse

sharkbite.com.au

CONVERSION FITTINGS



VERSATILITY, EFFICIENCY & RELIABILITY

Whether Copper, PEX or Polybutylene, SharkBite® has you covered with a comprehensive range of piping system adaptors that will ensure easy connection to most systems.




PEX FITTINGS




- Used to connect SharkBite® PEX Pipe
- PEX fittings have mustard coloured ends
- Fittings are rotatable after connection
- Fittings can be installed on wet pipe even with water flowing
- Fittings can be disconnected and reconnected as required

INSTALLATION OF PEX PIPE




Cut

Using SharkBite® PEX Pipe Cutters, cut the pipe squarely between two of the SharkBite® safe seal indicator marks as shown in the picture. Ensure pipe is round, clean and free of debris.




Push

Insert the pipe through the release collar to rest against the grab ring. Push the pipe firmly with a twisting action and push to the SharkBite® safe seal indicator mark.



Done

Ensure the SharkBite® safe seal indicator mark aligns with the release collar as shown.



Disassembly

Using the Disassembly Clip, fittings can be easily changed, removed and the fittings reused.

INSTALLATION FOR PEX AND COPPER PIPE ARE AS PER AS 3500

COPPER FITTINGS




- Used to connect copper systems
- Copper fittings have black coloured ends
- A range of fittings and adaptors are available
- Fittings are rotatable after connection
- Fittings can be installed on wet pipe even with water flowing
- Fittings can be disconnected and reconnected as required

INSTALLATION OF COPPER PIPE




Cut

Using a pipe cutter, cut the copper tube to length making sure the pipe is cut squarely. Ensure pipe is round, clean and free of debris.




Deburr

Remove burrs from the pipe using the SharkBite® deburrer and depth gauge.




Mark

Mark the pipe with a marker using the depth gauge.




Push

Insert the pipe by pushing firmly until a positive click is heard.



Done

Ensure the mark made with depth gauge aligns with the release collar.



Disassembly

Using the Disassembly Clip, fittings can be easily changed, removed and the fittings reused.

PEX FITTINGS



SharkBite® PEX fittings and ball valves comply with and are approved to Australian standards AS/NZS 2537 and WMTS-012 respectively.



PEX Flare Adaptors
F610XA 16mm OD x 15mm (½") BSP Male Threaded Flare



Female Elbows
F308XA 16mm OD x 15mm (½") BSP Female Threaded



Straight Couplings
F008XA 16mm OD x 16mm OD
F016XA 20mm OD x 20mm OD



Equal Tees
F362XA 16mm OD x 16mm OD x 16mm OD
F370XA 20mm OD x 20mm OD x 20mm OD



Female Backplated Elbows
F334XA 16mm OD x 15mm (½") BSP Female Threaded



Reducing Couplings
F058XA 20mm OD x 16mm OD



Unequal Tees
F412XA 20mm OD x 20mm OD x 16mm OD
F454XA 20mm OD x 16mm OD x 16mm OD



Male Backplated Elbows
F350XA 16mm OD x 15mm (½") BSP Male Threaded, 75mm
F351XA 16mm OD x 15mm (½") BSP Male Threaded, 185mm
F352XA 16mm OD x 15mm (½") BSP Male Threaded, 100mm
F354XA 20mm OD x 20mm (¾") BSP Female Threaded, 185mm



Straight Female Connectors
F072XA 16mm OD x 15mm (½") BSP Female Threaded
F088XA 20mm OD x 20mm (¾") BSP Female Threaded



Elbows
F248XA 16mm OD x 16mm OD
F256XA 20mm OD x 20mm OD



Stop Ends
F514XA 16mm OD
F518XA 20mm OD



Straight Male Connectors
F120XA 16mm OD x 15mm (½") BSP Male Threaded
F134XA 20mm OD x 20mm (¾") BSP Male Threaded



Male Elbows
F280XA 16mm OD x 15mm (½") BSP Male Threaded



Ball Valves
F670XA 16mm OD x 16mm OD
F672XA 20mm OD x 20mm OD
F680XA 16mm OD x 15mm (½") BSP Female Threaded

COPPER FITTINGS



SharkBite® Copper fittings and ball valves comply with and are approved to Australian standards AS 3688 and WMTS-012 respectively.



Slip Couplings
RA3008XA DN15 Cu x DN15 Cu
RA3016XA DN20 Cu x DN20 Cu



Male Lugged Elbows
RA350XA DN15 Cu x 15mm (½") BSP Male Threaded, 75mm



Straight Couplings
RA008XA DN15 Cu x DN15 Cu
RA016XA DN20 Cu x DN20 Cu



Equal Tees
RA362XA DN15 Cu x DN15 Cu x DN15 Cu
RA370XA DN20 Cu x DN20 Cu x DN20 Cu



Stop Ends
RA514XA DN15 Cu
RA518XA DN20 Cu



Reducing Couplings
RA058XA DN20 Cu x DN15 Cu



Unequal Tees
RA412XA DN20 Cu x DN20 Cu x DN15 Cu



Ball Valves
RA670XA DN15 Cu x DN15 Cu
RA672XA DN20 Cu x DN20 Cu



Female Connectors
RA072XA DN15 Cu x 15mm (½") BSP Female Threaded
RA088XA DN20 Cu x 20mm (¾") BSP Female Threaded



Elbows
RA248XA DN15 Cu x DN15 Cu
RA256XA DN20 Cu x DN20 Cu



Male Connectors
RA120XA DN15 Cu x 15mm (½") BSP Male Threaded
RA134XA DN20 Cu x 20mm (¾") BSP Male Threaded



Female Lugged Elbows
RA334XA DN15 Cu x 15mm (½") BSP Female Threaded
RA340XA DN20 Cu x 20mm (¾") BSP Female Threaded

CONVERSION FITTINGS - PEX TO COPPER



SharkBite® PEX to Copper fittings comply with and are approved to Australian standards AS/NZS 2537.



PEX to Copper Couplings
F009XA 16mm OD x DN15 Cu
F017XA 20mm OD x DN20 Cu



PEX to Copper Elbows
F250XA 16mm OD x DN15 Cu
F258XA 20mm OD x DN20 Cu



PEX to Copper SharkBite Centre Tees*
F364XA DN15 Cu x DN15 Cu x 16mm OD

*Copper must comply to AS 1432

PIPE



Potable Water (Mustard)
XF860A 16mm OD - 2.4m Straight
XF862A 16mm OD - 25m Coil
XF870A 20mm OD - 2.4m Straight
XF872A 20mm OD - 25m Coil



Tube Clips
F824A 16mm OD Tek Screw
F834A 20mm OD Tek Screw



Tube Cutters
F701A Universal



Disassembly Clips
F710AP 16mm OD and 20mm OD
RA712AP DN15 Cu and DN20 Cu



Copper Deburrers & Depth Gauges
F702A DN15 Cu, DN20 Cu, DN25 Cu



SharkBite® PEX pipe complies with and is approved to Australian standards AS 2492.