



Peel Stop

Chemwatch Material Safety Data Sheet
Issue Date: 9-Sep-2010
XC9317SC

Hazard Alert Code: MODERATE

CHEMWATCH 24-7409
Version No:2.0
CD 2011/2 Page 1 of 6

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

Peel Stop

PRODUCT USE

Water-based clear binding primer and sealer.

SUPPLIER

Company: Rust- Oleum Australia
Address:
Unit 1 , 2 Park Road
Rydalmere
NSW 2116
Australia
Telephone: + 612 9684 6060
Emergency Tel: **1800 039 008**
Fax: + 612 9680 0111


Company: Rust- Oleum Corporation (Manufacturer)
Address:
11 Hawthorn Parkway
Vernon Hills
Illinois 60061
United States of America

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

NON-HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. According to NOHSC Criteria, and ADG Code.
COMBUSTIBLE LIQUID, regulated under AS1940 for Bulk Storage purposes only.

CHEMWATCH HAZARD RATINGS



RISK

- Ingestion may produce health damage*.
 - Cumulative effects may result following exposure*.
- * (limited evidence).

SAFETY

- Do not breathe gas/fumes/vapour/spray.
- Avoid contact with skin.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
ethylene glycol	107-21-1	<3
non hazardous other ingredients		balance

Note: Manufacturer has supplied full ingredient information to allow CHEMWATCH assessment.

continued...

Peel Stop

Chemwatch Material Safety Data Sheet
Issue Date: 9-Sep-2010
XC9317SC

Hazard Alert Code: MODERATE

CHEMWATCH 24-7409
Version No:2.0
CD 2011/2 Page 2 of 6

Section 4 - FIRST AID MEASURES

SWALLOWED

- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

EYE

- If this product comes in contact with eyes:
- Wash out immediately with water.
- If irritation continues, seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin or hair contact occurs:
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes, aerosols or combustion products are inhaled remove from contaminated area.
- Other measures are usually unnecessary.

NOTES TO PHYSICIAN

- For acute or short term repeated exposures to ethylene glycol:
- Early treatment of ingestion is important. Ensure emesis is satisfactory.
- Test and correct for metabolic acidosis and hypocalcaemia.
- Apply sustained diuresis when possible with hypertonic mannitol.
- Evaluate renal status and begin haemodialysis if indicated. [I.L.O].

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Prevent, by any means available, spillage from entering drains or water course.
- Use water delivered as a fine spray to control fire and cool adjacent area.

FIRE/EXPLOSION HAZARD

- Combustible.
 - Slight fire hazard when exposed to heat or flame.
 - Heating may cause expansion or decomposition leading to violent rupture of containers.
 - On combustion, may emit toxic fumes of carbon monoxide (CO).
- Combustion products include: carbon dioxide (CO₂), other pyrolysis products typical of burning organic material.
May emit poisonous fumes.

FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

HAZCHEM

None

PERSONAL PROTECTION

Glasses:
Chemical goggles.

Gloves:
PVC chemical resistant type.

Respirator:
Type A- P Filter of sufficient capacity

continued...

Peel Stop

Chemwatch Material Safety Data Sheet
Issue Date: 9-Sep-2010
XC9317SC

Hazard Alert Code: MODERATE

CHEMWATCH 24-7409
Version No:2.0
CD 2011/2 Page 3 of 6

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.

MAJOR SPILLS

- Moderate hazard.
- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.

SUITABLE CONTAINER

- Metal can or drum
- Packaging as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

- Avoid reaction with oxidising agents.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- No smoking, naked lights or ignition sources.
- Store in a cool, dry, well-ventilated area.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	TWA F/CC	Notes
Australia Exposure Standards	ethylene glycol (Ethylene glycol vapour)	20	52	40	104				Sk
Australia Exposure Standards	ethylene glycol (Ethylene glycol particulate)		10						Sk

PERSONAL PROTECTION

continued...

Peel Stop

Hazard Alert Code: MODERATE

Chemwatch Material Safety Data Sheet
Issue Date: 9-Sep-2010
XC9317SC

CHEMWATCH 24-7409
Version No:2.0
CD 2011/2 Page 4 of 6

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION



RESPIRATOR

• Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

EYE

- Safety glasses with side shields
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent].

HANDS/FEET

- Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: such as:
 - frequency and duration of contact,
 - chemical resistance of glove material,
 - glove thickness and
 - dexterity.
- Wear chemical protective gloves, eg. PVC.
- Wear safety footwear or safety gumboots, eg. Rubber.

OTHER

- Overalls.
- P.V.C. apron.
- Barrier cream.
- Skin cleansing cream.

ENGINEERING CONTROLS

■ Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

White colour liquid with mild odour; mixes with water.

PHYSICAL PROPERTIES

Liquid.
Mixes with water.

State	Liquid	Molecular Weight	Not Applicable
Melting Range (°C)	0 approx	Viscosity	2000- 4000 cPs cSt@ 23°C
Boiling Range (°C)	100 approx	Solubility in water (g/L)	Miscible
Flash Point (°C)	>93	pH (1% solution)	Not Available
Decomposition Temp (°C)	Not Available	pH (as supplied)	8.0
Autoignition Temp (°C)	Not Available	Vapour Pressure (kPa)	Not Available
Upper Explosive Limit (%)	Not Available	Specific Gravity (water=1)	1.08

continued...

Peel Stop

Hazard Alert Code: MODERATE

Chemwatch Material Safety Data Sheet
Issue Date: 9-Sep-2010
XC9317SC

CHEMWATCH 24-7409
Version No:2.0
CD 2011/2 Page 5 of 6

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Lower Explosive Limit (%)	Not Available	Relative Vapour Density (air=1)	Not Available
Volatile Component (%vol)	Not Available	Evaporation Rate	Not Available
ethylene glycol			
log Kow (Prager 1995):		- 1.36	
log Kow (Sangster 1997):		- 1.36	

Section 10 - STABILITY AND REACTIVITY

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
 - Product is considered stable.
 - Hazardous polymerisation will not occur.
- For incompatible materials - refer to Section 7 - Handling and Storage.*

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

- Ingestion may produce health damage*.
- * (limited evidence).

CHRONIC HEALTH EFFECTS

- Cumulative effects may result following exposure*.
- * (limited evidence).

TOXICITY AND IRRITATION

- Not available. Refer to individual constituents.

SKIN

ethylene glycol	Australia Exposure Standards - Skin	Notes	Sk
-----------------	-------------------------------------	-------	----

Section 12 - ECOLOGICAL INFORMATION

No data

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
Peel Stop	No Data Available	No Data Available		
ethylene glycol	LOW	MED	LOW	HIGH

Section 13 - DISPOSAL CONSIDERATIONS

■ Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction.
- DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.

continued...

Peel Stop

Chemwatch Material Safety Data Sheet
Issue Date: 9-Sep-2010
XC9317SC

Hazard Alert Code: MODERATE

CHEMWATCH 24-7409
Version No:2.0

CD 2011/2 Page 6 of 6

Section 13 - DISPOSAL CONSIDERATIONS

- Bury or incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION



Labels Required: COMBUSTIBLE LIQUID, regulated under AS1940 for Bulk Storage purposes only.

HAZCHEM:

None (ADG7)

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: UN, IATA, IMDG

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE S5

REGULATIONS

Regulations for ingredients

ethylene glycol (CAS: 107-21-1) is found on the following regulatory lists;

"Australia Exposure Standards", "Australia Hazardous Substances", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "Australia National Pollutant Inventory", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix C", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "IMO Provisional Categorization of Liquid Substances - List 2: Pollutant only mixtures containing at least 99% by weight of components already assessed by IMO", "International Council of Chemical Associations (ICCA) - High Production Volume List", "International Fragrance Association (IFRA) Survey: Transparency List"

No data for Peel Stop (CW: 24-7409)

Section 16 - OTHER INFORMATION

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:
www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 9-Sep-2010
Print Date: 3-Aug-2011

This is the end of the MSDS.