

OCTOBER 2020

metallon **xL**™

Boral metallon xL™ engineered flooring envelopes the earthy beauty of timber flooring and contemporary aesthetics of precious metals, creating a synergy that is truly indulgent.

Engineered Flooring

With click lock installation, metallon $\mathbf{x}\mathbf{L}^{\mathrm{TM}}$ seamlessly integrates into your space. Pre-finishing minimises the extra work required and allows for versatility with its ability to be sanded back to reveal a more natural Blackbutt finish.

- Available in beautiful Australian Blackbutt
- No mess and fumes from sanding and finishing
- Low sheen high quality European UV cured acrylic lacquer
- Minimum 100gsm film build, for better wearability
- Easy installation over multiple surface types
- Features the UNICLIC® locking system on all four sides
- Unique colour and grain variations to suit any requirements
- Graded to AS 2796.2 Standard and better PEFC Certified

Specifications

Size	186mm x 14mm
Board Lengths	up to 2200mm
Film Build	Min 100gsm
Wear Layer (Nominal)	4mm
Grade	Standard and Better
Species	Blackbutt





Colours



Aztec White



Sterling









Quicksilver

Copper **Tungsten**

Installation

metallon xL™ engineered flooring can be glued or "floated" over any level subfloor such as a concrete slab, particleboard or plywood sheeting or over old timber floors or tiles.



PRODUCT GUIDE



metallon **xL**™



Care & Maintenance

With regular care and maintenance, you can enjoy a lifetime of beauty with your metallon $\mathbf{XL}^{\text{\tiny{TM}}}$ floor.

- For daily cleaning, use dry methods such as vacuuming and sweeping. To remove stubborn dirt, use a well-rung mop and a pH neutral cleaner. Do not clean timber floors with a steam mop.
- Place doormats at entrances, non-slip rugs in high-wear areas and protective pads under furniture legs.
- Do not use any abrasive brushes, steel wool, soap detergents or ammonia based cleaners.
- Always take care when moving appliances and furniture by placing them on a sturdy mat to slide into position.







Promoting sustainable forest management

Note: Variations within a timber species are normal, therefore photographs, samples and displays can only be indicative of colour and should not be used for final selection. It is normal for natural timber products to react to changes in atmospheric and environmental conditions such as humidity and temperature. This is considered normal. It is recommended that these species are viewed at a timber flooring showroom before a decision is made on colour. Cover colour is Aztec White.

www.boral.com.au/metallonXL

National free call 1800 818 317

