



MORE THAN CONCRETE

0800 ASK CEMIX

TILING & FLOORING

Dec 2022 | Page 1



PRE-MIXED GROUT

EASY TO APPLY GROUT FOR INTERIOR AND EXTERIOR WALLS AND FLOORS

AVAILABLE SIZE: 800gm



SCAN FOR DETAILS

DESCRIPTION:

CEMIX® PRE-MIXED GROUT is a ready mixed, easy to apply grout. It is suitable for walls and floors in interior and exterior applications. Its non-cracking formula contains anti-mould protection.

TYPICAL USES:

- Grouting joints from 1mm to 5mm wide.
- Suitable for most types of tiles.

ADVANTAGES:

- Ready and easy to use
- Anti-mould formula
- Variety of colours available

YIELD:

Varies according to the joint width and tile size.

STANDARDS:

All workmanship must be carried out in accordance with AS3958.1.

PREPARATION:

Before grouting, check ease of cleaning from the face of the tile being used. The surface should be clean and free of loose and friable material. The tile adhesive should be well cured before applying the grout.

MIXING:

No mixing required.

APPLICATION:

1. Shake the bottle well.
2. Cut the tapered nozzle to the width of the desired grout width.

3. Apply the grout into the joints by holding the bottle at a 90° angle.
4. Using a rubber float or squeegee, ensure the grout is forced into the joints.
5. Scrape any excess away with a rubber float or squeegee.
6. Allow the grout to firm for 15 minutes.
7. Immediately after applying the grout, remove any excess grout from the tile surface by working diagonally across the joints. Use minimal water and ensure the sponge is frequently rinsed. Do not allow the grout to dry on the tile surface.
8. Once the grout has hardened (approximately 6 to 24 hours), buff and polish the tile surface with a clean dry cloth.

Note: When grouting in external areas, ensure the grouted area is protected from any extreme weather conditions until full cure is reached after 7 days.

DRYING & CURING:

The initial set is after 24 hours at 23°C and 50% relative humidity.

Shower walls can be exposed to water from this time. Shower floors should be left to cure for 3 days before being exposed to water.

The grout will reach full cure after 7 days. Allow longer for lower temperatures, high relative humidity or denser tiles.

CLEANING:

Clean tools with water immediately after use.

STORAGE & SHELF LIFE:

Up to 12 months when stored in the original, unopened packaging, in a dry place at 23°C and 50% relative humidity.



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars

Repairs & Grouts

Admixtures

Decorative Sealers

Waterproofing

Tiling & Flooring



MORE THAN CONCRETE

0800 ASK CEMIX

TILING & FLOORING

Dec 2022 | Page 2

PRE-MIXED GROUT

LIMITATIONS:

Not suitable for use in water immersion application i.e. showers, baths, swimming pools, spas ect. Depending on application, some concavity may occur in wider joints. Shade variation and efflorescence are caused by factors beyond the manufacturer's control. This can include nature of cement, job site conditions, finishing techniques and uneven drying conditions.

If your project requires Building Consent, please email info@cemix.co.nz about the suitability of this product before use.

Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

DANGER



DISCLAIMER:

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX® PRODUCTS LTD does not give any warranty expressed or implied as to suitability for any particular use. For all advice concerning the use or suitability of this product for a particular application, please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD, who will refund or replace it at no cost, in accordance with the requirements of the Consumer Guarantees Act.



FOR MORE PRODUCT DETAILS:

CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061
AUCKLAND NEW ZEALAND
0800 ASK CEMIX | +64 09 636 1000
WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pinterest/CemixNZ



YouTube/CemixVideos



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars

Repairs & Grouts

Admixtures

Decorative Sealers

Waterproofing

Tiling & Flooring