



RYOBI is a trademark of Ryobi Limited, and is used under license.

4 892210 214058 >

Explore the range at:
ryobi.com.au ryobi.co.nz

Want to show off your project or tool collection? Tag @ryobiau or @ryobinz in your photos and videos on social media using the hashtag #ryobimade for your chance to feature!

Get social with us!
@ryobiau / @ryobinz



Rotary Tool (RRT4)
2.0Ah 4V Lithium-Ion Battery

- Voltage : 4 V
- No Load Speed : 5,000-25,000 RPM
- Collet Size : 1/8"
- Weight : 0.225 kg
- Capacity : 2.0 Ah
- Lithium-Ion Technology



Accessories Included:

Quick-Change Collet provides easy accessory changes.

Powered by the RYOBI USB Lithium battery. System for portability and minimal downtime.

Results dependent on tool, battery and application.

2.0Ah = 20 mins



RYOBI



Rotary Tool Kit



Includes
2.0Ah Lithium-Ion USB Cable RRT4K

Get social with us!
@ryobiau / @ryobinz



Want to show off your project or tool collection? Tag @ryobiau or @ryobinz in your photos and videos on social media using the hashtag #ryobimade for your chance to feature!

Explore the range at:
ryobi.com.au ryobi.co.nz

Compact Lightweight Design
Ideal for engraving, sanding and polishing

Quick Change Collet
Provides easy and quick accessory changes

Portability And Minimal Downtime
Powered by the RYOBI USB Lithium battery system for portability and minimal downtime

RYOBI

RYOBI



RYOBI

V 4 V

R.P.M. 5000-25000 min⁻¹

0.225 kg

4 892210 214058 >

Techtronic Industries Australia Pty Ltd
Techtronic Industries N.Z. Limited
MADE IN P.R.C.
www.ryobi.com.au www.ryobi.co.nz



Includes
2.0Ah Lithium-Ion USB Cable RRT4K



Rotary Tool Kit

Compact Lightweight Design
Ideal for engraving, sanding and polishing

Quick Change Collet
Provides easy and quick accessory changes

Portability And Minimal Downtime
Powered by the RYOBI USB Lithium battery system for portability and minimal downtime



*Standard 4 year warranty, with an additional 2 year warranty available subject to online registration within 30 days of purchase. For full applicable warranty details, please refer to the warranty card inside the box.

Get social with us!
@ryobiau / @ryobinz



Want to show off your project or tool collection? Tag @ryobiau or @ryobinz in your photos and videos on social media using the hashtag #ryobimade for your chance to feature!

Explore the range at:
ryobi.com.au ryobi.co.nz

RYOBI



Rotary Tool Kit



Includes
2.0Ah Lithium-Ion USB Cable RRT4K



Compact Lightweight Design
Ideal for engraving, sanding and polishing

Quick Change Collet
Provides easy and quick accessory changes

Portability And Minimal Downtime
Powered by the RYOBI USB Lithium battery system for portability and minimal downtime

6 YEAR TOOL REPLACEMENT WARRANTY



*Standard 4 year warranty, with an additional 2 year warranty available subject to online registration within 30 days of purchase. For full applicable warranty details, please refer to the warranty card inside the box.

EDITION : A

Update Detail: Removed "4V" from the description for global alignment as ANZ latest request.

SCALE : 100%

	P/N	910007526	MODEL NO	011254004(RRT4K)_ANZ	COLOR	CMYK+PMS388C
	Item ID	CC00	VENDOR			Total: 5C
	Rev.	03	ECN #	ECN-CC00	MATERIAL	350gsm+K3(B flute; 350gsm+112gsm+ 250gsm)
	SIZE	222x56x131mm(+/-2mm)	DATE	2023.03.06	ADHESIVE:	<input type="checkbox"/> Permanent acrylic <input type="checkbox"/> Removable acrylic

Graphic Designer Approved By: Jenny.Huang	Electrical Engineer Approved By:	Quality Assurance Approved By:	Eng. Manager Approved By: Mike.zong	Legal Depart Approved By:	FINISHING
					<input checked="" type="checkbox"/> Calendering coating (Gloss level: 60-70 GU) <input type="checkbox"/> Aqueous coating (Kraft paper) (Gloss level: 5-10 GU)

REMARK	LAB READING (Measured by X-Rite instrument. Condition: M0, illuminant: D50, 2 degree)
1. The light fastness of printing ink: Grade 6 or above (油墨耐晒需达到6级或以上)	<input type="checkbox"/> PMS 158C(Std) L:61.1 a:41.69 b:59.61 ΔE< 2.5 (ΔE*76)
2. (If Any) Bar code grading: GS1 standard, Grade B or above 条码(如果有)需要满足GS1标准且扫描需达到B级或以上	<input type="checkbox"/> PMS 158C(Kraft) L:61.61 a:42.04 b:51.91 ΔE< 3.0 (ΔE*76)
	<input checked="" type="checkbox"/> PMS 388C L:86.29 a:-17.2 b:78.24 ΔE< 3.0 (ΔE*76)
	<input type="checkbox"/> PMS 485C L:47.36 a:71.42 b:60.7 ΔE< 3.0 (ΔE*76)

Die Cut Displayed in Blue Color