



Reinforcing Fabric

Non-woven, polyester fabric for strengthening membranes.

DESCRIPTION

Crommelin[®] Reinforcing Fabric is a non-woven, rot proof polyester fabric for use in conjunction with liquid waterproofing membranes. It is easier to wet out and possesses superior flexibility to materials such as fibreglass.

FEATURES AND BENEFITS

- Bridges Gaps.
- Strengthens membranes by increasing tensile strength and puncture resistance.
- Flexible.
- Easy to wet out.
- Outstanding conformability.
- High grab tensile strength.

AREAS OF USE

Reinforcing Fabric is suitable for use in the following areas:

- Around Pipes & Penetrations.
- Internal Corners.
- External Corners.
- Over Cracks & Construction Joints.

SUITABLE SUBSTRATES

Reinforcing Fabric is suitable for use on the following surfaces:

- As applicable to waterproofing membrane being applied.

APPLICATION PROCESS

Full application instructions can be found at www.crommelin.com.au/full-instructions/

- It is essential to ensure the fabric is well embedded into the first coat of waterproofing membrane whilst the membrane is wet, and thoroughly wetted out.
- Allow to dry thoroughly before application of coat 2.
- Follow all instructions of waterproofing membrane being applied.

Note: If Reinforcing Fabric remains visible after the application of the second coat of waterproofing membrane, further coats of membrane are required to ensure optimum film build.

SIZES

Reinforcing Fabric is available in the following sizes;

- 100mm x 10M
- 100mm x 50M
- 200mm x 20M
- 200mm x 50m

PRECAUTIONS

- Where **Reinforcing Fabric** is used, drying times of waterproof membrane may be increased.
- For areas with excessive movement such as construction joints, to meet AS3740 Waterproofing Wet Areas Within Residential Buildings it is essential to use a bond breaking reinforcing fabric such as **Crommelin[®] Reinforcing Fabric with Bond Breaker** or **Crommelin[®] Contractor Polyurethane Sealant** or **Crommelin[®] Silicone WP Plus**.

TRANSPORT AND STORAGE

- | | | | |
|-------------------|--------------------|------------------------|-------------------------|
| • Size: 100mmx10m | • Weight: 0.1kg | • Cool and Dry Storage | • UN Number: N/A |
| 100mmx50m | 0.3kg | | |
| 200mmx20m | 0.25kg | | |
| 200mmx50m | 0.6kg | | |
| • DG Class: N/A | • Flash Point: N/A | • Hazchem Code: N/A | • Poisons Schedule: N/A |

Crommelin[®] and other marks followed by ® are registered trademarks.

Any advice, recommendation, information, assistance or service provided by Crommelin[®] in relation to its products or their use is given in good faith, however is provided without responsibility or liability.

Customers need to undertake their own assessment to determine the suitability of a product for the intended use. As the performance of any product is subject to a wide variety of different surface types as well as environmental and surface-specific conditions, it is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs as required on the specific surface.

Crommelin[®] also reserves the right to update information without prior notice, to reflect ongoing research and product development.