



Panels SpecRite™

Manufactured For Results.

MULTI-USE TIMBER PANEL
MERBAU HARDWOOD
1200 x 405 x 18
Length (mm) Width (mm) Thickness (mm)



Select
Grade



Kiln Dried
Timber



Class A Bond Glue
(Weather Resistant)

- > Suitable for indoor and outdoor applications including bench tops, shelving and furniture.
- > Store the panel flat, off the ground and protected from weather and extreme changes in humidity.
- > When installing, ensure sufficient space is left to allow the wood to expand to prevent deformation when humidity changes.
- > Seal all sides of the panel with an appropriate treatment - oil, wax or lacquer before use.
- > Select grade, kiln dried timber for stability and a high quality, clean appearance.
- > Naturally resistant to fungi and insects like termites and dry wood borers.
- > Finger jointed and laminated using weather-resistant, class A bond glue
- > Use caution when using in wet areas, follow the instructions provided.
- > Installation and care instructions on the back of this label.
- > **WARNING: Merbau has tannin, a naturally occurring substance, please see overleaf for further instructions.**



8 994851 000697

Made in Indonesia
Item No. 8330195
GW: 7.4 Kg

Merbau's superior strength and stability are attributable to its tannin-rich properties, resulting in low shrinkage and minimal surface and end splitting. Tannin is a naturally occurring substance in timber which will leach the first few times it is exposed to moisture. If left unsealed tannin will leach from the product staining timber, tiled areas and other nearby surfaces. Objects left on the timber surface can also draw tannin out, creating surface marks. We strongly recommend sealing all sides of the board with 3 coats of an appropriate treatment of oil, wax or lacquer before use.